

Lineal Surface



Lineal surface 1400 White 2320lm 3000K Ra>80 DALI-2 / Push Dim

Article code: 8246095897
EAN: 5703821180412



Electrical

System wattage: 21W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 15, B16: 24, C10: 25, C16: 41
Leakage current (mA): 0.29

Light technic

Type of light source: LED
Luminous flux: 2320lm
Efficacy: 110 lm/W
Colour temperature: 3000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L80/B10>100,000
Lifetime: L93/>50,000
Light distribution: Direct
UGR: UGR<26
Photobiological safety: RG 0

Control/Dimming

Type: DALI-2 / Push Dim

Protection

Luminaire class: Class I
IK Class: IK08
IP Class: IP20

Energy and approvals

Contains light source of energy class: D
Breeam: Fulfil Hea 01 for flicker free lighting
BVB: Yes

Materials and finish

Housing: Aluminium
Colour: White (RAL 9003)

Mounting/Connection


Mounting: Surface, Indoor
Module: 1400
Connection: 5-pole Winsta mini with 5x2,5mm2 through wiring

Dimensions


Length (mm) L: 1401
Width (mm) W: 42
Height (mm) H: 70
Weight (kg) gross/net: 3.5 / 3.3

Packaging

Packing dimensions (mm): 1560 x 50 x 80



Module	W	H	L1	L2
840mm	42	70	841	891
1120mm	42	70	1121	1171
1400mm	42	70	1401	1451
End cap	42	70	3	28



5 7 0 3 8 2 1 1 8 0 4 1 2