


Junistar Lux



Junistar Lux White 620lm 4000K Ra 98 Trailing edge

Article code: 902502
EAN: 7021989025023



Electrical

Wattage: 7W
System wattage: 8W
Voltage: 220-240V
Frequency (Hz): 50/60Hz
Max. luminaires per circuit breaker: B10: 105, B16: 168, C10: 105, C16: 168

Light technic

Type of light source: LED
Luminous flux: 620lm
Efficacy: 78 lm/W
Colour temperature: 4000K
Colour rendering (Ra): Ra 98
MacAdams factor: SDCM: 1
Lifetime: L90/B10>100,000
Light distribution: Direct
Optic: Reflector
Beam angle: 42°
UGR: UGR<22

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class II SELV
IP Class: IP44/IP20

Energy and approvals

Contains light source of energy class: F
Breeam: Fulfil Hea 01 for flicker free lighting
BVB: Yes
Sunda Hus: C-

Materials and finish

Housing: Aluminium
Colour: White (RAL 9003)
Optics: Tempered glass

Mounting/Connection



Mounting: Recessed, Indoor
Connection: Screwless terminal block

Dimensions

Height (mm) H: 50
Diameter (mm) D: 94
Cut-out (mm): 83
Ceiling void depth (mm): 48
Weight (kg) gross/net: 0.395 / 0.325

Packaging

Packing dimensions (mm): 130 x 115 x 75



7 0 2 1 9 8 9 0 2 5 0 2 3