

## Junistar Soft Black 740lm 2700K Ra 98 Trailing edge / Linect

Article code: 903213  
EAN: 7021989032137



### Electrical

Wattage: 9W  
System wattage: 11W  
Voltage: 220-240V  
Frequency (Hz): 50/60Hz  
Max. luminaires per circuit breaker: B10: 77, B16: 123, C10: 77, C16: 123

### Light technic

Type of light source: LED  
Luminous flux: 740lm  
Efficacy: 67 lm/W  
Colour temperature: 2700K  
Colour rendering (Ra): Ra 98  
MacAdams factor: SDCM: 2  
Lifetime: L90/B10>100,000  
Light distribution: Direct  
Optic: Reflector  
Beam angle: 42°  
UGR: UGR<19  
Photobiological safety: RG 1

### Control/Dimming

Type: Trailing edge / Linect

### Protection

Luminaire class: Class II SELV  
IP Class: IP54/IP20

### Energy and approvals

Contains light source of energy class: E  
Breeam: Fulfils Hea 01 for flicker free lighting  
BVB: Yes

### Materials and finish

Housing: Aluminium  
Colour: Black (RAL 9004)  
Optics: Tempered glass

### Mounting/Connection

Mounting: Recessed, Indoor / Outdoor  
Connection: 3 pol Linect / screwless terminal block

### Dimensions

Height (mm) H: 53  
Diameter (mm) D: 94  
Cut-out (mm): 83  
Ceiling void depth (mm): 51  
Distance to flammable materials: 10mm  
Weight (kg) gross/net: 0.46 / 0.41

### Packaging

Packing dimensions (mm): 130 x 115 x 85

