

Junistar Soft TW



Junistar Soft TW White 650lm (@4000K) 2000-4000K Ra>90 TW LEDDim

Article code: 903321
EAN: 7021989033219



Electrical

System wattage: 11W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 74, B16: 118, C10: 74, C16: 118

Light technic

Type of light source: LED
Luminous flux: 650lm (@4000K)
Efficacy: 59 lm/W
Colour temperature: 2000-4000K
Colour rendering (Ra): Ra>90
MacAdams factor: SDCM: 2
Lifetime: L90/B10>100,000
Light distribution: Direct
Optic: Reflector
Beam angle: 42°
Photobiological safety: RG 1

Control/Dimming

Type: TW LEDDim

Protection

Luminaire class: Class II SELV
IP Class: IP54/IP20

Energy and approvals

Contains light source of energy class: F
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium
Colour: White (RAL 9003)
Optics: Tempered glass

Mounting/Connection



Mounting: Recessed, Indoor / Outdoor
Connection: Screwless terminal block

Dimensions

Height (mm) H: 53
Diameter (mm) D: 94
Cut-out (mm): 83
Ceiling void depth (mm): 51
Distance to flammable materials: 10mm
Weight (kg) gross/net: 0.46 / 0.43

Packaging

Packing dimensions (mm): 130 x 115 x 85



7 0 2 1 9 8 9 0 3 3 2 1 9