

Junistar Eco IsoSafe



Junistar ECO Isosafe Black 580lm 2700K Ra>90 Trailing edge

Article code: 905216
EAN: 7021989052166



Electrical

Wattage: 6W
System wattage: 7W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 105, B16: 168, C10: 105, C16: 168

Light technic

Type of light source: LED
Luminous flux: 580lm
Efficacy: 83 lm/W
Colour temperature: 2700K
Colour rendering (Ra): Ra>90
MacAdams factor: SDCM: 2
Lifetime: L90/B10>100,000
Light distribution: Direct
Optic: Reflector
Beam angle: 42°
UGR: UGR<22

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class II SELV
IP Class: IP44

Energy and approvals

Contains light source of energy class: E
Breeam: Fulfils Hea 01 for flicker free lighting
BVB: Yes
Passed 60-minute fire resistance test in accordance with EN 13652: Yes
Second insulation test passed according to EN ISO 10140-2:2021 and 10140-3:2021 part E: Yes
SOUNDING: C-

Materials and finish

Housing: Aluminium
Colour: Black (RAL 9004)
Optics: Tempered glass

Mounting/Connection



Mounting: Recessed, Indoor
Connection: Screwless terminal block

Dimensions

Height (mm) H: 40
Diameter (mm) D: 90
Cut-out (mm): 83
Weight (kg) gross/net: 2.85 / 0.361

Packaging

Packing dimensions (mm): 390 x 240 x 105
Number per pack: 8



7 0 2 1 9 8 9 0 5 2 1 6 6