


Junistar Sun White IsoSafe 570lm 2700K Ra>95 Trailing edge

Article code: 905500
EAN: 7021989055006



Electrical

System wattage: 7.5W
Voltage: 220-240V
Frequency (Hz): 50/60Hz
Max. luminaires per circuit breaker: B10: 19, B16: 30, C10: 31, C16: 51

Light technic

Type of light source: LED
Luminous flux: 570lm
Efficacy: 76 lm/W
Colour temperature: 2700K
Colour rendering (Ra): Ra>95
MacAdams factor: SDCM: 2
Lifetime: L90/B10>100,000
Light distribution: Direct
Optic: Reflector
Beam angle: 42°

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class II SELV
IP Class: IP44/IP20

Energy and approvals

Contains light source of energy class: F
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium
Colour: White (RAL 9003)
Optics: Tempered glass

Mounting/Connection



Mounting: Recessed, Indoor
Connection: Screwless terminal block

Dimensions

Height (mm) H: 56
Diameter (mm) D: 94
Cut-out (mm): 83
Ceiling void depth (mm): 54
Weight (kg) gross/net: 0.419 / 0.349

Packaging

Packing dimensions (mm): 115 x 115 x 95



7 0 2 1 9 8 9 0 5 5 0 0 6