

Cube DimToWarm



Cube White DimToWarm 550lm 2000-2800K Ra>95 Trailing edge

Article code: 906211
EAN: 7021989062110



Electrical

Wattage: 6W
System wattage: 7.3W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 19, B16: 30, C10: 31, C16: 51

Light technic

Type of light source: LED
Luminous flux: 550lm
Efficacy: 75 lm/W
Colour temperature: 2000-2800K
Colour rendering (Ra): Ra>95
MacAdams factor: SDCM: 3
Lifetime: L90/B10>50,000
Light distribution: Direct
Optic: Reflector
Beam angle: 42°
UGR: UGR<22

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class I
IP Class: IP21

Energy and approvals

Contains light source of energy class: F
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium and stainless steel
Colour: Matte white (RAL 9003)
Optics: Tempered glass

Mounting/Connection



Mounting: Surface, Indoor / Outdoor
Connection: Screwless terminal block

Dimensions

Length (mm) L: 132
Width (mm) W: 132
Height (mm) H: 65
Distance to flammable materials: 10mm
Weight (kg) gross/net: 0.9 / 0.79

Packaging

Packing dimensions (mm): 140 x 140 x 75



7 0 2 1 9 8 9 0 6 2 1 1 0