

# Jupiter Pro



## Jupiter Pro 1500 White 40° 1450lm 2700K Ra>90 Trailing edge

Article code: 912999  
EAN: 7021989129998



### Electrical

System wattage: 15W  
Voltage: 220-240V  
Max. luminaires per circuit breaker: B10: 19, B16: 30, C10: 31, C16: 51

### Light technic

Type of light source: LED  
Luminous flux: 1450lm  
Efficacy: 97 lm/W  
Colour temperature: 2700K  
Colour rendering (Ra): Ra>90  
MacAdams factor: SDCM: 2  
Lifetime: L90/B10>100,000  
Light distribution: Direct  
Optic: Reflector  
Beam angle: 40°  
UGR: UGR<22

### Control/Dimming

Type: Trailing edge

### Protection

Luminaire class: Class II SELV  
IP Class: IP65/IP20

### Energy and approvals

Contains light source of energy class: E  
Breeam: Fulfils Hea 01 for flicker free lighting

### Materials and finish

Housing: Aluminium  
Colour: Matte white (RAL 9003)  
Optics: Tempered glass

### Mounting/Connection

Mounting: Recessed, Indoor / Outdoor  
Module: 1500  
Connection: Screwless terminal block

### Dimensions

Height (mm) H: 112  
Diameter (mm) D: 114  
Cut-out (mm): 83  
Ceiling void depth (mm): 110  
Distance to flammable materials: 100mm  
Weight (kg) gross/net: 1.08 / 0.9

### Packaging

Packing dimensions (mm): 140 x 140 x 140

