

Callisto Graphite 190lm 2700K Ra>80 Trailing edge

Article code: 923012
EAN: 7021989230120



Electrical

System wattage: 3W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 115, B16: 184, C10: 134, C16: 215

Light technic

Type of light source: LED
Luminous flux: 190lm
Efficacy: 63 lm/W
Colour temperature: 2700K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L70/B50>50,000
Light distribution: Direct
Optic: Glass Clear
Beam angle: 65°

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class II
IK Class: IK06
IP Class: IP65

Energy and approvals

Contains light source of energy class: F
Breeam: Fulfils Hea 01 for flicker free lighting
BVB: Yes
ULOR (: Yes, when ceiling mounted

Materials and finish

Housing: Aluminium
Colour: Graphite
Optics: Tempered glass

Mounting/Connection



Mounting: Surface, Indoor / Outdoor
Connection: Screwless terminal block

Dimensions

Height (mm) H: 33
Diameter (mm) D: 110
Weight (kg) gross/net: 0.324 / 0.27

Packaging

Packing dimensions (mm): 120 x 115 x 45



7 0 2 1 9 8 9 2 3 0 1 2 0