

Lineal Surface Connect



Lineal surface 1120 White 1870lm 3000K Ra>80 Connect

Article code: 9341000818
EAN: 5703821207096



Electrical

System wattage: 17W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 26, B16: 42, C10: 44, C16: 70

Light technic

Type of light source: LED
Luminous flux: 1870lm
Efficacy: 110 lm/W
Colour temperature: 3000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L80/B10>100,000
Lifetime: L93/>50,000
Light distribution: Direct

Control/Dimming

Type: Connect

Protection

Luminaire class: Class I
IK Class: IK08
IP Class: IP20

Energy and approvals

Breem: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium
Colour: White (RAL 9003)

Mounting/Connection



Mounting: Surface, Indoor
Module: 1120

Dimensions


Length (mm) L: 1192
Width (mm) W: 42
Height (mm) H: 70
Weight (kg) gross/net: 2.8 / 2.3

Packaging

Packing dimensions (mm): 1350 x 47 x 85



	Minor movements		Major movements	
H (m)	X1 (m)	Y1 (m)	X2 (m)	Y2 (m)
2.4	1.9	2.9	2.9	4.3
3	2.4	3.6	3.6	5.4



5 7 0 3 8 2 1 2 0 7 0 9 6