


Jupiter Pro Soft



Jupiter Pro Soft White 1110lm 2700K Ra>90 Trailing edge

Article code: 940354
EAN: 7021989403548

• = This article is produced by order, with an expected delivery time of 3-4 weeks.



Electrical

System wattage: 15W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 19, B16: 30, C10: 31, C16: 51

Light technic

Type of light source: LED
Luminous flux: 1110lm
Efficacy: 74 lm/W
Colour temperature: 2700K
Colour rendering (Ra): Ra>90
MacAdams factor: SDCM: 2
Lifetime: L90/B10>100,000
Light distribution: Direct
Optic: Reflector
Beam angle: 35°

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class II SELV
IP Class: IP65/IP20

Energy and approvals

Contains light source of energy class: E
Breem: Fulfil Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium
Colour: White (RAL 9003)
Optics: Tempered glass

Mounting/Connection

Mounting: Recessed, Indoor / Outdoor
Connection: Quick connector

Dimensions

Height (mm) H: 130
Diameter (mm) D: 114
Cut-out (mm): 83
Distance to flammable materials: 50mm
Weight (kg) gross/net: 0.635 / 0.54

Packaging

Packing dimensions (mm): 152 x 143 x 140

