Jupiter Firerated

sg

Jupiter Firerated Brushed steel 350lm 2700K Ra>80 Trailing edge

Article code:	997420
EAN:	7021989974208

CE | ▣ | IP23 | ⌂

5 years WARRANTY

Electrical
System wattage:	5.5W
Voltage:	220-240V

Light technic
Type of light source:	LED
Socket:	GU10
Light source included:	Yes
Luminous flux:	350lm
Efficacy:	64 lm/W
Colour temperature:	2700K
Colour rendering (Ra):	Ra>80
MacAdams factor:	SDCM: 4
Lifetime:	L70/B50>50,000
Light distribution:	Direct
Beam angle:	25°

Control/Dimming
Type:	Trailing edge

Protection
Luminaire class:	Class II
IP Class:	IP23

Energy and approvals
Contains light source of energy class:	F

Materials and finish
Housing:	Steel
Colour:	Brushed steel

Mounting/Connection
Mounting:	Recessed, Indoor
Connection:	Screwless terminal block

Dimensions
Height (mm) H:	116
Diameter (mm) D:	100
Cut-out (mm):	83
Ceiling void depth (mm):	114
Distance to flammable materials:	50mm
Weight (kg) gross/net:	0.552 / 0.46

Packaging
Packing dimensions (mm):	125 x 110 x 100

114 mm | Ø76-Ø83 mm | Ø100 mm

cd/klm — C0/C180, C90/C270 — η = 99 %