

Herning Wall



A stylishly designed classic outdoor luminaire that is equally at home in urban and more rural settings. In solid powder-coated aluminium and with a tempered glass front, it is equally suitable in domestic or public settings. The glass front conceals access to switches for 3000K/4000K and for 2 lumen levels, i.e. 4 combinations in one product. By default, it is set to 3000K and the highest lumen level. Easy installation with wall bracket and quick connector. Multiple rear surface cable inputs plus punch-out entry points.

Herning Wall



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 623960 Herning Wall Black Mini 580/620/1220/1300lm 3000/4000K Ra>80 Trailing edge LED 73/78/72/76lm/W SDCM:3 L80/B20>50,000 Direct, Glass	Class II IP65 IK06	Trailing edge	Wall, Indoor / Outdoor Screwless terminal block	L331 x W182 x H181
 623962 Herning Wall Black Midi 1060/1140/1770/1920lm 3000/4000K Ra>80 Trailing edge LED 82/88/71/77lm/W SDCM:3 L80/B20>50,000 Direct, Glass	Class II IP65 IK06	Trailing edge	Wall, Indoor / Outdoor Screwless terminal block	L402 x W240 x H222
 623968 Herning Wall Corten Mini 580/620/1220/1300lm 3000/4000K Ra>80 Trailing edge LED 73/78/72/76lm/W SDCM:3 L80/B20>50,000 Direct, Glass	Class II IP65 IK06	Trailing edge	Wall, Indoor / Outdoor Screwless terminal block	L331 x W182 x H181
 623969 Herning Wall Corten Midi 1060/1140/1770/1920lm 3000/4000K Ra>80 Trailing edge LED 82/88/71/77lm/W SDCM:3 L80/B20>50,000 Direct, Glass	Class II IP65 IK06	Trailing edge	Wall, Indoor / Outdoor Screwless terminal block	L402 x W240 x H222
 623961 Herning Wall Grey Mini 580/620/1220/1300lm 3000/4000K Ra>80 Trailing edge LED 73/78/72/76lm/W SDCM:3 L80/B20>50,000 Direct, Glass	Class II IP65 IK06	Trailing edge	Wall, Indoor / Outdoor Screwless terminal block	L331 x W182 x H181
 623963 Herning Wall Grey Midi 1060/1140/1770/1920lm 3000/4000K Ra>80 Trailing edge LED	Class II IP65 IK06	Trailing edge	Wall, Indoor / Outdoor Screwless terminal block	L402 x W240 x H222
Accessories	LED			

Article codes



Article	82/88/71/77lm/W SDCM:3	Protection	Control gear	Mounting/Connection	Dimensions
L80/B20~50,000 Direct, Glass	623965				Ø176 x H3
	Herning Mini PC Diffuser				
	623967				Ø232 x H3
	Herning Midi PC Diffuser				