



Arena is an energy efficient surface mounted IP23 luminaire for use in industry and storage. It is easy to install with hinged gear tray, and can be mounted either direct on ceiling (screws) or by using the mounting hooks for horizontal wiring. Arena is available in two lengths and with three different light distributions. 5/7-pole terminal block with 5/7x2,5mm<sup>2</sup> through wiring. Cable entry in end caps through grommet.

## Product- and environment images









# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>8246092489</p> <p><b>Arena 1200 White Medium</b></p> <p><b>11720lm 4000K Ra&gt;80 DALI-2</b></p> <p><b>71W LED</b></p> <p>165 lm/W SDCM:3</p> <p>L90/B10&gt;70,000, L80/B20&gt;100,000</p> <p>Beam: Medium, Direct, Lens Medium</p>	<p><b>Class I</b></p> <p><b>IP23</b></p> <p><b>IK08</b></p>	DALI-2	<p>Suspended or surface, Indoor</p> <p>7-pole screwless terminal block with</p> <p>5x2,5mm<sup>2</sup> (+DALI) through wiring</p>	L1194 x W138 x H63
 <p>8246093530</p> <p><b>Arena 1200 White Medium 9000lm</b></p> <p><b>4000K Ra&gt;80 DALI-2</b></p> <p><b>57W LED</b></p> <p>158 lm/W SDCM:3</p> <p>L90/B10&gt;70,000, L80/B20&gt;100,000</p> <p>Beam: Medium, Direct, Lens Medium</p>	<p><b>Class I</b></p> <p><b>IP23</b></p> <p><b>IK08</b></p>	DALI-2	<p>Suspended or surface, Indoor</p> <p>7-pole screwless terminal block with</p> <p>5x2,5mm<sup>2</sup> (+DALI) through wiring</p>	L1194 x W138 x H63
 <p>8246093572</p> <p><b>Arena 1200 White Narrow</b></p> <p><b>9060/11910lm 4000K Ra&gt;80 DALI-2</b></p> <p><b>57W LED</b></p> <p>159 lm/W SDCM:3</p> <p>L90/B10&gt;70,000, L80/B20&gt;100,000</p> <p>Beam: Narrow, Direct, Lens Narrow</p>	<p><b>Class I</b></p> <p><b>IP23</b></p> <p><b>IK08</b></p>	DALI-2	<p>Suspended or surface, Indoor</p> <p>7-pole screwless terminal block with</p> <p>5x2,5mm<sup>2</sup> (+DALI) through wiring</p>	L1269 x W137 x H57
 <p>8246093598</p> <p><b>Arena 1200 White Wide</b></p> <p><b>8980/11800lm 4000K Ra&gt;80 DALI-2</b></p> <p><b>57W LED</b></p> <p>158 lm/W SDCM:3</p> <p>L90/B10&gt;70,000, L80/B20&gt;100,000</p> <p>Beam: Wide, Direct, Lens Wide</p>	<p><b>Class I</b></p> <p><b>IP23</b></p> <p><b>IK08</b></p>	DALI-2	<p>Suspended or surface, Indoor</p> <p>7-pole screwless terminal block with</p> <p>5x2,5mm<sup>2</sup> (+DALI) through wiring</p>	L1194 x W138 x H63
 <p>8246093873</p> <p><b>Arena 1200 White Medium</b></p> <p><b>23580lm 4000K Ra&gt;80 DALI-2</b></p> <p><b>144W LED</b></p> <p>164 lm/W SDCM:3</p> <p>L90/B10&gt;70,000, L80/B20&gt;100,000</p> <p>Beam: Medium, Direct, Lens Medium</p>	<p><b>Class I</b></p> <p><b>IP23</b></p> <p><b>IK08</b></p>	DALI-2	<p>Suspended or surface, Indoor</p> <p>7-pole screwless terminal block with</p> <p>5x2,5mm<sup>2</sup> (+DALI) through wiring</p>	L1256 x W295 x H57
 <p>8246093912</p> <p><b>Arena 1200 White Narrow 23530lm</b></p> <p><b>4000K Ra&gt;80 DALI-2</b></p> <p><b>144W LED</b></p> <p>163 lm/W SDCM:3</p> <p>L90/B10&gt;70,000, L80/B20&gt;100,000</p> <p>Beam: Narrow, Direct, Lens Narrow</p>	<p><b>Class I</b></p> <p><b>IP23</b></p> <p><b>IK08</b></p>	DALI-2	<p>Suspended or surface, Indoor</p> <p>7-pole screwless terminal block with</p> <p>5x2,5mm<sup>2</sup> (+DALI) through wiring</p>	L1256 x W295 x H57







# Article codes






Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>8246093938 •  <b>Arena 1200 White Wide 23230lm</b>  <b>4000K Ra&gt;80 DALI-2</b>  <b>144W LED</b>                      161 lm/W SDCM:3                      L90/B10&gt;70,000, L80/B20&gt;100,000                      Beam: Wide, Direct, Lens Wide</p>	<b>Class I</b> <b>IP23</b> <b>IK08</b>	DALI-2	Suspended or surface, Indoor 7-pole screwless terminal block with 5x2,5mm <sup>2</sup> (+DALI) through wiring	L1256 x W295 x H57
 <p>8246092476  <b>Arena 1200 White Medium</b>  <b>11830lm 4000K Ra&gt;80 On/Off</b>  <b>79W LED</b>                      150 lm/W SDCM:3                      L90/B10&gt;70,000, L80/B20&gt;100,000                      Beam: Medium, Direct, Lens Medium</p>	<b>Class I</b> <b>IP23</b> <b>IK08</b>	On/Off	Suspended or surface, Indoor 5-pole screwless terminal block with 5x2,5mm <sup>2</sup> through wiring	L1194 x W138 x H63
 <p>8246093527  <b>Arena 1200 White Medium 9000lm</b>  <b>4000K Ra&gt;80 On/Off</b>  <b>57W LED</b>                      158 lm/W SDCM:3                      L90/B10&gt;70,000, L80/B20&gt;100,000                      Beam: Medium, Direct, Lens Medium</p>	<b>Class I</b> <b>IP23</b> <b>IK08</b>	On/Off	Suspended or surface, Indoor 5-pole screwless terminal block with 5x2,5mm <sup>2</sup> through wiring	L1194 x W138 x H63
 <p>8246093569 •  <b>Arena 1200 White Narrow</b>  <b>9060/11910lm 4000K Ra&gt;80 On/Off</b>  <b>57W LED</b>                      159 lm/W SDCM:3                      L90/B10&gt;70,000, L80/B20&gt;100,000                      Beam: Narrow, Direct, Lens Narrow</p>	<b>Class I</b> <b>IP23</b> <b>IK08</b>	On/Off	Suspended or surface, Indoor 5-pole screwless terminal block with 5x2,5mm <sup>2</sup> through wiring	L1269 x W137 x H57
 <p>8246093860  <b>Arena 1200 White Medium</b>  <b>23580lm 4000K Ra&gt;80 On/Off</b>  <b>140W LED</b>                      168 lm/W SDCM:3                      L90/B10&gt;70,000, L80/B20&gt;100,000                      Beam: Medium, Direct, Lens Medium</p>	<b>Class I</b> <b>IP23</b> <b>IK08</b>	On/Off	Suspended or surface, Indoor 5-pole screwless terminal block with 5x2,5mm <sup>2</sup> through wiring	L1256 x W295 x H57
 <p>8246093909 •  <b>Arena 1200 White Narrow 23530lm</b>  <b>4000K Ra&gt;80 On/Off</b>  <b>140W LED</b>                      168 lm/W SDCM:3                      L90/B10&gt;70,000, L80/B20&gt;100,000                      Beam: Narrow, Direct, Lens Narrow</p>	<b>Class I</b> <b>IP23</b> <b>IK08</b>	On/Off	Suspended or surface, Indoor 5-pole screwless terminal block with 5x2,5mm <sup>2</sup> through wiring	L1256 x W295 x H57

# Article codes






Article		Protection	Control gear	Mounting/Connection	Dimensions
	8246093925  <b>Arena 1200 White Wide 23230lm</b> <b>4000K Ra&gt;80 On/Off</b> <b>140W LED</b> 166 lm/W SDCM:3 L90/B10>70,000, L80/B20>100,000 Beam: Wide, Direct, Lens Wide	<b>Class I</b> <b>IP23</b> <b>IK08</b>	On/Off	Suspended or surface, Indoor 5-pole screwless terminal block with 5x2,5mm <sup>2</sup> through wiring	L1256 x W295 x H57
	8246094212 <b>Arena 1200 White Wide 8980lm</b> <b>4000K Ra&gt;80 On/Off</b> <b>57W LED</b> 158 lm/W SDCM:3 L90/B10>70,000, L80/B20>100,000 Beam: Wide, Direct, Lens Wide	<b>Class I</b> <b>IP23</b> <b>IK08</b>	On/Off	Suspended or surface, Indoor 5-pole screwless terminal block with 5x2,5mm <sup>2</sup> through wiring	L1194 x W138 x H63
	8246094539 <b>Arena 1200 White Wide 11800lm</b> <b>4000K Ra&gt;80 On/Off</b> <b>79W LED</b> 149 lm/W SDCM:3 L90/B10>70,000, L80/B20>100,000 Beam: Wide, Direct, Lens Wide	<b>Class I</b> <b>IP23</b> <b>IK08</b>	On/Off	Suspended or surface, Indoor 5-pole screwless terminal block with 5x2,5mm <sup>2</sup> through wiring	L1194 x W138 x H63
	8246094762 <b>Arena 1500 White Wide 11800lm</b> <b>4000K Ra&gt;80 On/Off</b> <b>79W LED</b> 149 lm/W SDCM:3 L90/B10>70,000, L80/B20>100,000 Beam: Wide, Direct, Lens Wide	<b>Class I</b> <b>IP23</b> <b>IK08</b>	On/Off	Suspended or surface, Indoor 5-pole screwless terminal block with 5x2,5mm <sup>2</sup> through wiring	L1769 x W137 x H57
	8246094801 <b>Arena 1700 White Wide 16830lm</b> <b>4000K Ra&gt;80 On/Off</b> <b>113W LED</b> 149 lm/W SDCM:3 L90/B10>50,000 Beam: Wide, Direct, Lens Wide	<b>Class I</b> <b>IP23</b> <b>IK08</b>	On/Off	Suspended or surface, Indoor 5-pole screwless terminal block with 5x2,5mm <sup>2</sup> through wiring	L1842 x W137 x H59

## Accessories

	8249045174 <b>Shopline DALI White Adapter kit</b>	<b>Class I</b> <b>IP20</b>	Indoor Cable 5x0,75mm <sup>2</sup> 0,3m
	8249045187  <b>Shopline White Adapter kit</b>	<b>Class I</b> <b>IP20</b>	Indoor Cable 3x0,75mm <sup>2</sup> 0,3m

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 820259 <b>Start current limiter DIN 16A</b>				L90 x W18 x H58
 8249044900 <b>Wirekit 2x5m</b>				L19 x W25 x H150
 8249044913 <b>Mounting kit for adjustable angulation</b>				L100 x W98 x H95

• = This article is produced by order, with an expected delivery time of 3-4 weeks.