



Arena ECO is an energy saving and super practical LED luminaire for storage and industry. It is simple to install with a hinged gear tray, and can be mounted either directly into the ceiling (screws), or by using mounting hooks for horizontal wiring. Arena ECO is available in two lengths, for easy replacement of fluorescent tube lighting from 2x36W to 2x58W. Through wiring and cable connection provided at both ends. Linear lens optics maximises the light distribution. 5-pole terminal block with 5x2,5mm² through wiring. Cable entry in end caps trough grommet. Linear lens optics maximizes the light distribution. Narrow beam (30°) is available on request.

Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 607032 Arena ECO 1200 Wide 6710lm 3000K Ra>80 On/Off 47W LED 143 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 90°, Direct,	Class I IP23 IK10	On/Off	Surface, Indoor 5-pole screwless terminal block with 5x2,5mm² through wiring	L1184 x W134 x H72
 607033 Arena ECO 1500 Wide 9900lm 3000K Ra>80 On/Off 72W LED 138 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 90°, Direct,	Class I IP23 IK10	On/Off	Surface, Indoor 5-pole screwless terminal block with 5x2,5mm² through wiring	L1552 x W134 x H72
 607016 Arena ECO 1200 Wide 7100lm 4000K Ra>80 DALI-2 46W 154 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 90°, Direct,	Class I IP23 IK10	DALI-2	Surface, Indoor 7-pole screwless terminal block with 5x2,5mm² (+DALI) through wiring	L1184 x W134 x H72
 607017 Arena ECO 1200 Medium 11370lm 4000K Ra>80 DALI-2 76W 150 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 60°, Direct,	Class I IP23 IK10	DALI-2	Surface, Indoor 7-pole screwless terminal block with 5x2,5mm² (+DALI) through wiring	L1184 x W134 x H72
 607018 Arena ECO 1200 Wide 10960lm 4000K Ra>80 DALI-2 76W 144 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 90°, Direct,	Class I IP23 IK10	DALI-2	Surface, Indoor 7-pole screwless terminal block with 5x2,5mm² (+DALI) through wiring	L1184 x W134 x H72
 607019 Arena ECO 1500 Medium 11370lm 4000K Ra>80 DALI-2 76W 150 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 60°, Direct,	Class I IP23 IK10	DALI-2	Surface, Indoor 7-pole screwless terminal block with 5x2,5mm² (+DALI) through wiring	L1552 x W134 x H72

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 607020 Arena ECO 1500 Wide 10960lm 4000K Ra>80 DALI-2 76W 144 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 90°, Direct,	Class I IP23 IK10	DALI-2	Surface, Indoor 7-pole screwless terminal block with 5x2,5mm² (+DALI) through wiring	L1552 x W134 x H72
 607008 Arena ECO 1200 Wide 7100lm 4000K Ra>80 On/Off 46W LED 154 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 90°, Direct,	Class I IP23 IK10	On/Off	Surface, Indoor 5-pole screwless terminal block with 5x2,5mm² through wiring	L1184 x W134 x H72
 607009 Arena ECO 1200 Medium 11370lm 4000K Ra>80 On/Off 76W LED 150 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 60°, Direct,	Class I IP23 IK10	On/Off	Surface, Indoor 5-pole screwless terminal block with 5x2,5mm² through wiring	L1184 x W134 x H72
 607010 Arena ECO 1200 Wide 10960lm 4000K Ra>80 On/Off 76W LED 144 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 90°, Direct,	Class I IP23 IK10	On/Off	Surface, Indoor 5-pole screwless terminal block with 5x2,5mm² through wiring	L1184 x W134 x H72
 607011 Arena ECO 1500 Medium 11370lm 4000K Ra>80 On/Off 76W LED 150 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 60°, Direct,	Class I IP23 IK10	On/Off	Surface, Indoor 5-pole screwless terminal block with 5x2,5mm² through wiring	L1552 x W134 x H72
 607012 Arena ECO 1500 Wide 10960lm 4000K Ra>80 On/Off 76W LED 144 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 90°, Direct,	Class I IP23 IK10	On/Off	Surface, Indoor 5-pole screwless terminal block with 5x2,5mm² through wiring	L1552 x W134 x H72

Accessories

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	8249045174 Shopline DALI White Adapter kit	Class I IP20		Indoor Cable 5x0,75mm ² 0,3m	
	8249045187 • Shopline White Adapter kit	Class I IP20		Indoor Cable 3x0,75mm ² 0,3m	
	820259 Start current limiter DIN 16A				L90 x W18 x H58
	8249044900 Wirekit 2x5m				L19 x W25 x H150
	8249044913 Mounting kit for adjustable angulation				L100 x W98 x H95

• = This article is produced by order, with an expected delivery time of 3-4 weeks.