

Rax 200



Recessed mounted LED downlight. Made of fire-resistant polycarbonate. SDCM 2. L90/B10>100,000, Supplied with 3000K/4000K LED. Complete with driver and quick connection between driver and downlight for super quick and easy mounting. Can be mounted to ceiling panels with a thickness of 1-50 mm. The luminaire comes complete with ceiling ring RAL9010 gloss 25 made of die-cast aluminium. Matt reflector.

Rax 200



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>8246081254 • Rax 200 3490lm 3000K Ra>80 On/Off 31W LED 113 lm/W SDCM:2 L90/B10>100,000 Beam: 79°, Direct, Satin Matt Reflector</p>	Class I IP20	On/Off	Recessed, Indoor	Ø223 x L223 x W223 x H107
 <p>8246079651 • Rax 200 3610lm 4000K Ra>80 DALI-2 / Push Dim 31W LED 116 lm/W SDCM:2 L90/B10>100,000 Beam: 79°, Direct, Satin Matt Reflector</p>	Class I IP20	DALI-2 / Push Dim	Recessed, Indoor	Ø223 x L223 x W223 x H107
Accessories				
 <p>212618 Rax 200 Black Rehabring Ø205-250mm</p>				Ø270 x H16
 <p>212619 Rax 200 Black Rehabring Ø210-280mm</p>				Ø300 x H16
 <p>8249045035 Rax 200 Black frontring</p>				L224 x W24 x H10
 <p>8249044696 Rax 200 White Rehabring Ø205-250mm</p>				Ø270 x H16
 <p>8246094429 Emergencybox Driver DALI / EM Self test, DALI Emergency 3 hours</p>				L270 x W75 x H35
 <p>8246094364 Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours</p>				L270 x W75 x H35
 <p>8246094500 Emergencybox Driver DALI / EM DALI/Self test, Emergency 3 hours</p>				L270 x W75 x H35

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 8249038725 Rax 200 Mounting plate				L585 x W260 x H15
 8249043532 • Rax 200 Mounting ring				L265 x W265 x H70
 8249044476 • Rax 200				L265 x W265 x H70

• = This article is produced by order, with an expected delivery time of 3-4 weeks.