

Sense IP65



Sense IP65 is an all-round luminaire for use in places such as industrial kitchens, hospitals, laboratories and production facilities. It has a very high lumen output and fantastic colour rendering with $Ra > 90$ and low glare with UGR

Sense IP65



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>8246096346 • SENSE IP65 595x595 White 4840lm 3000K Ra>90 DALI Emergency 3 hours 43W LED 113 lm/W SDCM:3 L80/B50>100,000, L90/B10>50,000 Direct, Prism Optic</p>	Class I IP54/IP65 IK07	DALI Emergency 3 hours	Recessed, Indoor Cable 5x0,75mm ² 2,5m Halogen free	L595 x W595 x H94
 <p>8246096359 SENSE IP65 595x595 White 4830lm 3000K Ra>80 DALI Emergency 3 hours 43W LED 112 lm/W SDCM:3 L80/B50>100,000, L90/B10>50,000 Direct, Prism Optic</p>	Class I IP54/IP65 IK07	DALI Emergency 3 hours	Recessed, Indoor Cable 5x0,75mm ² 2,5m Halogen free	L595 x W595 x H94
 <p>8246096304 SENSE IP65 595x595 White 4840lm 3000K Ra>90 DALI-2 / Push Dim 43W LED 113 lm/W SDCM:3 L80/B50>100,000, L90/B10>50,000 Direct, Prism Optic</p>	Class I IP54/IP65 IK07	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm ² 2,5m Halogen free	L595 x W595 x H94
 <p>8246096317 • SENSE IP65 595x595 White 4830lm 3000K Ra>80 DALI-2 / Push Dim 43W LED 112 lm/W SDCM:3 L80/B50>100,000, L90/B10>50,000 Direct, Prism Optic</p>	Class I IP54/IP65 IK07	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm ² 2,5m Halogen free	L595 x W595 x H94
 <p>8246096265 SENSE IP65 595x595 White 5110lm 4000K Ra>90 DALI Emergency 3 hours 49W LED 104 lm/W SDCM:3 L80/B50>100,000, L90/B10>50,000 Direct, Prism Optic</p>	Class I IP54/IP65 IK07	DALI Emergency 3 hours	Recessed, Indoor Cable 5x0,75mm ² 2,5m Halogen free	L595 x W595 x H94
 <p>8246096281 SENSE IP65 599x599 White 5110lm 4000K Ra>90 DALI Emergency 3 hours 49W LED 104 lm/W SDCM:3 L80/B50>100,000, L90/B10>50,000</p>	Class I IP54/IP65 IK07	DALI Emergency 3 hours	Recessed, Indoor Cable 5x0,75mm ² 2,5m Halogen free	L599 x W599 x H93

Article codes



Article	Direct, Prism Optic	Protection	Control gear	Mounting/Connection	Dimensions
	8246096362 • SENSE IP65 595x595 White 5060lm 4000K Ra>80 DALI Emergency 3 hours 43W LED 118 lm/W SDCM:3 L80/B50>100,000, L90/B10>50,000 Direct, Prism Optic	Class I IP54/IP65 IK07	DALI Emergency 3 hours	Recessed, Indoor Cable 5x0,75mm ² 2,5m Halogen free	L595 x W595 x H94
	8246096375 SENSE IP65 599x599 White 5060lm 4000K Ra>80 DALI Emergency 3 hours 43W LED 118 lm/W SDCM:3 L80/B50>100,000, L90/B10>50,000 Direct, Prism Optic	Class I IP54/IP65 IK07	DALI Emergency 3 hours	Recessed, Indoor Cable 5x0,75mm ² 2,5m Halogen free	L599 x W599 x H93
	8246096100 SENSE IP65 595x595 White 5120lm 4000K Ra>90 DALI-2 / Push Dim 38W LED 135 lm/W SDCM:3 L80/B50>100,000, L90/B10>50,000 Direct, Prism Optic	Class I IP54/IP65 IK07	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm ² 2,5m Halogen free	L595 x W595 x H94
	8246096278 • SENSE IP65 599x599 White 5120lm 4000K Ra>90 DALI-2 / Push Dim 38W LED 135 lm/W SDCM:3 L80/B50>100,000, L90/B10>50,000 Direct, Prism Optic	Class I IP54/IP65 IK07	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm ² 2,5m Halogen free	L599 x W599 x H93
	8246096320 • SENSE IP65 595x595 White 5060lm 4000K Ra>80 DALI-2 / Push Dim 43W LED 118 lm/W SDCM:3 L80/B50>100,000, L90/B10>50,000 Direct, Prism Optic	Class I IP54/IP65 IK07	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm ² 2,5m Halogen free	L595 x W595 x H94
	8246096333 • SENSE IP65 599x599 White 5050lm 4000K Ra>80 DALI-2 / Push Dim 43W LED 117 lm/W SDCM:3 L80/B50>100,000, L90/B10>50,000 Direct, Prism Optic	Class I IP54/IP65 IK07	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm ² 2,5m Halogen free	L599 x W599 x H93

Accessories



8249044557

L625 x W625 x H55

625x625 White Plaster board/Troldtekt Recessed frame

• = *This article is produced by order, with an expected delivery time of 3-4 weeks.*