



DiLED IV is a for recessed mounted luminaire for most known ceiling systems in different modules. DiLED IV is suitable for office and general lighting indoor. The opal/prismatic optic front ensures a uniformly lit surface. Complete with driver and quick connection between driver and luminaire for super quick and easy mounting. Supplied with different color temperature with on/off or Dali control. Emergency units for easy connection to the luminaire as extra accessories.

Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>8246094827 • DiLED IV 595x595 White 4040lm 4000K Ra>80 DALI-2 33W LED 122 lm/W SDCM:3 L85/B10100,000 Direct, Prism Optic</p>	Class II IP20	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	L595 x W595 x H60
 <p>8246094830 • DiLED IV 599x599 White 4040lm 4000K Ra>80 DALI-2 33W LED 122 lm/W SDCM:3 L85/B10100,000 Direct, Prism Optic</p>	Class II IP20	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	L599 x W599 x H60
 <p>8246094843 • DiLED IV 584x584 White 4040lm 4000K Ra>80 DALI-2 33W LED 122 lm/W SDCM:3 L85/B10100,000 Direct, Prism Optic</p>	Class II IP20	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	L584 x W584 x H60
 <p>8246094911 • DiLED IV 595x595 White 2240lm 4000K Ra>80 DALI-2 LED L85/B10100,000 Direct, Prism Optic</p>		DALI-2	Indoor	L595 x W595 x H60
 <p>8246094940 • DiLED IV 599x599 White 2240lm 4000K Ra>80 DALI-2 18W LED 124 lm/W SDCM:3 L85/B10100,000 Direct, Prism Optic</p>	Class II IP20	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	L599 x W599 x H60
 <p>8246094979 • DiLED IV 584x584 White 2240lm 4000K Ra>80 DALI-2 18W LED 124 lm/W SDCM:3 L85/B10100,000 Direct, Prism Optic</p>	Class II IP20	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	L584 x W584 x H60

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>8246095004 • DiLED IV 595x595 White 4430lm 4000K Ra>80 DALI-2 33W LED 134 lm/W SDCM:3 L85/B10100,000 Direct, Opal</p>	Class II IP20	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	L595 x W595 x H60
 <p>8246095020 • DiLED IV 599x599 White 4430lm 4000K Ra>80 DALI-2 33W LED 134 lm/W SDCM:3 L85/B10100,000 Direct, Opal</p>	Class II IP20	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	L599 x W599 x H60
 <p>8246095046 • DiLED IV 584x584 White 4430lm 4000K Ra>80 DALI-2 33W LED 134 lm/W SDCM:3 L85/B10100,000 Direct, Opal</p>	Class II IP20	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	L584 x W584 x H60
 <p>8246094908 • DiLED IV 595x595 White 2240lm 4000K Ra>80 On/Off LED L85/B10100,000 Direct, Prism Optic</p>		On/Off	Indoor	L595 x W595 x H60
 <p>8246094924 • DiLED IV 595x595 White 4040lm 4000K Ra>80 On/Off 33W LED 122 lm/W SDCM:3 L85/B10100,000 Direct, Prism Optic</p>	Class II IP20	On/Off	Recessed, Indoor 5 pol Linect / screwless terminal block	L595 x W595 x H60
 <p>8246094937 • DiLED IV 599x599 White 2240lm 4000K Ra>80 On/Off 18W LED 124 lm/W SDCM:3 L85/B10100,000 Direct, Prism Optic</p>	Class II IP20	On/Off	Recessed, Indoor 5 pol Linect / screwless terminal block	L599 x W599 x H60

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>8246094953 • DiLED IV 599x599 White 4040lm 4000K Ra>80 On/Off 33W LED 122 lm/W SDCM:3 L85/B10100,000 Direct, Prism Optic</p>	Class II IP20	On/Off	Recessed, Indoor 5 pol Linect / screwless terminal block	L599 x W599 x H60
 <p>8246094966 • DiLED IV 584x584 White 2240lm 4000K Ra>80 On/Off 18W LED 124 lm/W SDCM:3 L85/B10100,000 Direct, Prism Optic</p>	Class II IP20	On/Off	Recessed, Indoor Screwless terminal block	L584 x W584 x H60
 <p>8246094995 • DiLED IV 595x595 White 4430lm 4000K Ra>80 On/Off 33W LED 134 lm/W SDCM:3 L85/B10100,000 Direct, Opal</p>	Class II IP20	On/Off	Recessed, Indoor 5 pol Linect / screwless terminal block	L595 x W595 x H60
 <p>8246095017 • DiLED IV 599x599 White 4430lm 4000K Ra>80 On/Off 33W LED 134 lm/W SDCM:3 L85/B10100,000 Direct, Opal</p>	Class II IP20	On/Off	Recessed, Indoor 5 pol Linect / screwless terminal block	L599 x W599 x H60
 <p>8246095033 • DiLED IV 584x584 White 4430lm 4000K Ra>80 On/Off 33W LED 134 lm/W SDCM:3 L85/B10100,000 Direct, Opal</p>	Class II IP20	On/Off	Recessed, Indoor 5 pol Linect / screwless terminal block	L584 x W584 x H60
 <p>8246094982 • DiLED IV 584x584 4040lm 4000K Ra>80 On/Off 33W LED 122 lm/W SDCM:3 L85/B10100,000 Direct, Prism Optic</p>	Class II IP20	On/Off	Recessed, Indoor 5 pol Linect / screwless terminal block	L584 x W584 x H60

Accessories

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 8249044557 625x625 White Plaster board/Troldtekt Recessed frame				L625 x W625 x H55
 8246094429 Emergencybox Driver DALI / EM Self test, DALI Emergency 3 hours				L270 x W75 x H35
 8246094364 Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours				L270 x W75 x H35
 8246094500 Emergencybox Driver DALI / EM DALI/Self test, Emergency 3 hours				L270 x W75 x H35

• = This article is produced by order, with an expected delivery time of 3-4 weeks.