

Facet




Slim, minimalistic luminaire with direct/indirect light. Perfect for offices and over desks with glare-free optic in PMMA. Delivered with 2,5 meter cable and 2x2 meter suspension wires. Quick installation with plug and play solution.

Product- and environment images



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	8246093394	Class I	Dim (down) 1x pull switch sensor	Suspended, Indoor	L1514 x W64 x H80
	Facet Black 5030lm 3000K Ra>80 Dim (down) 1x pull switch sensor (up/down) 35W LED 144 lm/W SDCM:3 L80/B10>100,000, L94>50,000 Direct/Indirect 50/50%, Lens C, prismatic Conical	IP20	(up/down)	2x2m wire kit w/loop M4 Cable 3x0,75mm² 2,5m w/ Schuko white	
	8246094241	Class I	Dim 1x pull switch	Suspended, Indoor	L1164 x W64 x H80
	Facet Black 3240lm 3000K Ra>80 Dim 1x pull switch 23W LED 141 lm/W SDCM:3 L80/B10>100,000, L94>50,000 Direct/Indirect 60/40%, Lens C, prismatic Conical	IP20		2x2m wire kit w/loop M4 Cable 3x0,75mm² 2,5m w/ Schuko white	
	8246094254	Class I	Dim 1x pull switch	Suspended, Indoor	L1444 x W64 x H80
	Facet Black 5030lm 3000K Ra>80 Dim 1x pull switch 35W LED 144 lm/W SDCM:3 L80/B10>100,000, L94>50,000 Direct/Indirect 50/50%, Lens C, prismatic Conical	IP20		2x2m wire kit w/loop M4 Cable 3x0,75mm² 2,5m w/ Schuko white	
	8246086084	Class I	2x pull switch, on/off	Suspended, Indoor	L1164 x W64 x H80
	Facet White 3240lm 3000K Ra>80 2x pull switch, on/off 23W LED 141 lm/W SDCM:3 L80/B10>100,000, L94>50,000 Direct/Indirect 60/40%, Lens C, prismatic Conical	IP20		2x2m wire kit w/loop M4 Cable 3x0,75mm² 2,5m w/ Schuko white	
	8246082499	Class I	DALI-2 / Push Dim	Suspended, Indoor	L1164 x W64 x H80
	Facet White 3240lm 3000K Ra>80 DALI-2 / Push Dim 23W LED 141 lm/W SDCM:3 L80/B10>100,000, L94>50,000 Direct/Indirect 60/40%, Lens C, prismatic Conical	IP20		2x2m wire kit w/loop M4 Cable 5x0,75mm² 2,5m white	

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	8246094270	Class I	DALI-2 / Push Dim	Suspended, Indoor	L1444 x W64 x H80
	Facet White 5030lm 3000K Ra>80	IP20		2x2m wire kit w/loop M4	
	DALI-2 / Push Dim			Cable 5x0,75mm ² 2,5m white	
	35W LED				
	144 lm/W SDCM:3 L80/B10>100,000, L94>50,000 Direct/Indirect 50/50%, Lens C, prismatic Conical				
	8246090355	Class I	Dim (down) 1x pull	Suspended, Indoor	L1514 x W64 x H80
	Facet White 5030lm 3000K Ra>80	IP20	switch sensor	2x2m wire kit w/loop M4	
	Dim (down) 1x pull switch sensor		(up/down)	Cable 3x0,75mm ² 2,5m w/ Schuko	
	(up/down)			white	
	35W LED 144 lm/W SDCM:3 L80/B10>100,000, L94>50,000 Direct/Indirect 50/50%, Lens C, prismatic Conical				
	8246086097	Class I	Dim 1x pull switch	Suspended, Indoor	L1164 x W64 x H80
	Facet White 3240lm 3000K Ra>80	IP20		2x2m wire kit w/loop M4	
	Dim 1x pull switch			Cable 3x0,75mm ² 2,5m w/ Schuko	
	23W LED 141 lm/W SDCM:3 L80/B10>100,000, L94>50,000 Direct/Indirect 60/40%, Lens C, prismatic Conical			white	
	8246086042	Class I	On/Off	Suspended, Indoor	L1164 x W64 x H80
	Facet White 3240lm 3000K Ra>80	IP20		2x2m wire kit w/loop M4	
	On/Off			Cable 3x0,75mm ² 2,5m w/ Schuko	
	23W LED 141 lm/W SDCM:3 L80/B10>100,000, L94>50,000 Direct/Indirect 60/40%, Lens C, prismatic Conical			white	
	8246094267	Class I	On/Off	Suspended, Indoor	L1444 x W64 x H80
	Facet White 5030lm 3000K Ra>80	IP20		2x2m wire kit w/loop M4	
	On/Off			Cable 3x0,75mm ² 2,5m w/ Schuko	
	35W LED 144 lm/W SDCM:3 L80/B10>100,000, L94>50,000 Direct/Indirect 50/50%, Lens C, prismatic Conical			white	

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	8246096090 Facet Black 5250lm 4000K Ra>80 Dim 1x pull switch 35W LED 150 lm/W SDCM:3 L80/B10>100,000, L94>50,000 Direct/Indirect 50/50%, Lens C, prismatic Conical	Class I IP20	Dim 1x pull switch	Suspended, Indoor 2x2m wire kit w/loop M4 Cable 3x0,75mm ² 2,5m w/ Schuko white	L1444 x W64 x H80
	8246086068 Facet White 3380lm 4000K Ra>80 DALI-2 / Push Dim 23W LED 147 lm/W SDCM:3 L80/B10>100,000, L94>50,000 Direct/Indirect 60/40%, Lens C, prismatic Conical	Class I IP20	DALI-2 / Push Dim	Suspended, Indoor 2x2m wire kit w/loop M4 Cable 5x0,75mm ² 2,5m white	L1164 x W64 x H80
	8246087449  Facet White 4890lm 4000K Ra>80 DALI-2 / Push Dim 34W LED 144 lm/W SDCM:3 L80/B10>100,000, L94>50,000 Direct/Indirect 65/35%, Lens C, prismatic Conical	Class I IP20	DALI-2 / Push Dim	Suspended, Indoor 2x2m wire kit w/loop M13 Cable 5x0,75mm ² 2,5m white	L1444 x W64 x H80
	8246090342 Facet White 5250lm 4000K Ra>80 Dim (down) 1x pull switch sensor (up/down) 35W LED 150 lm/W SDCM:3 L80/B10>100,000, L94>50,000 Direct/Indirect 50/50%, Lens C, prismatic Conical	Class I IP20	Dim (down) 1x pull switch sensor (up/down)	Suspended, Indoor 2x2m wire kit w/loop M4 Cable 3x0,75mm ² 2,5m w/ Schuko white	L1514 x W64 x H80
	8246096074 Facet White 3380lm 4000K Ra>80 Dim 1x pull switch 23W LED 147 lm/W SDCM:3 L80/B10>100,000, L94>50,000 Direct/Indirect 60/40%, Lens C, prismatic Conical	Class I IP20	Dim 1x pull switch	Suspended, Indoor 2x2m wire kit w/loop M4 Cable 3x0,75mm ² 2,5m w/ Schuko white	L1164 x W64 x H80

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 8246096087 Facet White 5250lm 4000K Ra>80 Dim 1x pull switch 35W LED 150 lm/W SDCM:3 L80/B10>100,000, L94>50,000 Direct/Indirect 50/50%, Lens C, prismatic Conical	Class I IP20	Dim 1x pull switch	Suspended, Indoor 2x2m wire kit w/loop M4 Cable 3x0,75mm² 2,5m w/ Schuko white	L1444 x W64 x H80
 8246086055 Facet White 3380lm 4000K Ra>80 On/Off 23W LED 147 lm/W SDCM:3 L80/B10>100,000, L94>50,000 Direct/Indirect 60/40%, Lens C, prismatic Conical	Class I IP20	On/Off	Suspended, Indoor 2x2m wire kit w/loop M4 Cable 3x0,75mm² 2,5m w/ Schuko white	L1164 x W64 x H80
Accessories				
 212198 Black T-carrier ceiling bracket				L30 x W20 x H5
 212255 T-profil White Suspension Rail 600mm				L596 x W35 x H17
 8249044007 Facet II White Wall bracket kit				L490 x W70 x H70
 820307 Emergency battery 3 Hours 3.0Ah - Model No: B093				L137 x W27 x H27

• = This article is produced by order, with an expected delivery time of 3-4 weeks.