



DiLED IV TW is a recessed mounted luminaire for most known ceiling systems in different modules. DiLED IV TW is suitable for office and general lighting indoor. The opal or prismatic optic front ensures a uniformly lit surface. Complete with driver and quick connection between driver and luminaire for super quick and easy mounting. Tunable White 2700-6500K DALI Type 8. Emergency box to be ordered separately.

## Product- and environment images



# Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	8246095156 • <b>DiLED Iv 595x595 White 3320lm</b> <b>2700-6500K Ra&gt;80 TW DALI Type 8</b> <b>35W LED</b> 95 lm/W SDCM:3 L90/B50>100,000, L95>50,000 Direct, Prism Optic	<b>Class II</b> <b>IP20</b>	TW DALI Type 8	Indoor 5 pol Linect / screwless terminal block	L595 x W595 x H60
	8246095169 • <b>DiLED Iv 599x599 White 3320lm</b> <b>2700-6500K Ra&gt;80 TW DALI Type 8</b> <b>35W LED</b> 95 lm/W SDCM:3 L90/B50>100,000, L95>50,000 Direct, Prism Optic	<b>Class II</b> <b>IP20</b>	TW DALI Type 8	Indoor	L599 x W599 x H60

• = This article is produced by order, with an expected delivery time of 3-4 weeks.