

EcoLine Office TW



Flat design, powder-coated white RAL9010 gloss 25. Double parabolic reflector and diffuser with option of dimmable solution (DALI/SwitchDim). Plug-and-play solution for quick installation. Adjustable wire suspension (2x2 m) ordered as accessory. Tunable White from 2700 Kelvin to 6500 Kelvin white light. Controlled by Dali Type 8.

EcoLine Office TW



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>8246091985 EcoLine Office TW 1200 White 4600lm 2700-6500K Ra>80 TW DALI Type 8 41W LED 112 lm/W SDCM:3 L90/B10>50,000 Direct/Indirect 60/40%, Double parabolic louvre, satin matt</p>	Class I IP20	TW DALI Type 8	Suspended, Indoor 2x2m wire kit w/loop M13 w/2 brackets Screwless terminal block	L1200 x W142 x H81
Accessories				
 <p>212255 T-profil White Suspension Rail 600mm</p>				L596 x W35 x H17
 <p>212048 EcoLine Office accessories 1200 Asymmetric bracket with wirekit</p>				L1050 x W135 x H40
 <p>212049 EcoLine Office accessories Wire kit</p>				L2000
 <p>6049000874 EcoLine Office accessories Mounting kit for suspension rail</p>				
 <p>8249042724 [•] Ceiling box 2x2m Wire kit</p>				L180 x W120 x H10

[•] = This article is produced by order, with an expected delivery time of 3-4 weeks.