EcoLine Office TW





Flat design, powder-coated white RAL9010 gloss 25. Double parabolic reflector and diffuser with option of dimmable solution (DALI/SwitchDim). Plug-and-play solution for quick installation. Adjustable wire suspension (2x2 m) ordered as accessory. Tunable White from 2700 Kelvin to 6500 Kelvin white light. Controlled by Dali Type 8.

EcoLine Office TW



Product- and environment images











Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
0	8246091985	Class I	TW DALI Type 8	Suspended, Indoor	L1200 x W142 x H81
	EcoLine Office TW 1200 White	IP20		2x2m wire kit w/loop M13 w/2	
	4600lm 2700-6500K Ra>80 TW DALI			brackets	
	Type 8			Screwless terminal block	
	41W LED				
	112 lm/W SDCM:3				
	L90/B10>50,000				
	Direct/Indirect 60/40%, Double				
	parabolic louvre, satin matt				
Accessories					
	212255				L596 x W35 x H17
	T-profil White Suspension Rail 600m	nm			
1.	212048				L1050 x W135 x H40
Oll	EcoLine Office accessories 1200 Asy	mmetric bracket w	ith wirekit		
	212049				L2000
	EcoLine Office accessories Wire kit				
III	6049000874				
	EcoLine Office accessories Mountin	g kit for suspensior	ı rail		
X	8249042724				

^{• =} This article is produced by order, with an expected delivery time of 3-4 weeks.