

# Lineal Suspended



Lineal Suspended is a modular system solution for suspended installation. Lineal provides an efficient and uniform lighting experience, and is supplied with both upward and downward lighting. The range comes in the standard colours black and white. The opalprism front on the roll ensures seamless light without joints. SG also delivers customised solutions beyond the standard product range. For each continuous line, you need one or more straight lines and/or corners, a starter kit and a front foil.

# Lineal Suspended



## Product- and environment images



# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>8246094607</p> <p><b>Lineal suspended 840 Black</b></p> <p><b>2360lm 3000K Ra&gt;80 DALI-2 / Push</b></p> <p><b>Dim</b></p> <p><b>21W LED</b></p> <p>112 lm/W SDCM:3</p> <p>L80/B10&gt;100,000, L93/&gt;50,000</p> <p>Direct/Indirect 50/50%,</p>	<p><b>Class I</b></p> <p><b>IP20</b></p> <p><b>IK08</b></p>	<p>DALI-2 / Push Dim</p>	<p>Suspended, Indoor</p> <p>1x2m wire kit w/ceiling bracket</p> <p>5-pole Winsta mini with 5x1,5mm2 through wiring</p>	<p>L841 x W42 x H70</p>
 <p>8246094623</p> <p><b>Lineal suspended 1120 Black</b></p> <p><b>3300lm 3000K Ra&gt;80 DALI-2 / Push</b></p> <p><b>Dim</b></p> <p><b>29W LED</b></p> <p>114 lm/W SDCM:3</p> <p>L80/B10&gt;100,000, L93/&gt;50,000</p> <p>Direct/Indirect 50/50%,</p>	<p><b>Class I</b></p> <p><b>IP20</b></p> <p><b>IK08</b></p>	<p>DALI-2 / Push Dim</p>	<p>Suspended, Indoor</p> <p>1x2m wire kit w/ceiling bracket</p> <p>5-pole Winsta mini with 5x1,5mm2 through wiring</p>	<p>L1121 x W42 x H70</p>
 <p>8246094649</p> <p><b>Lineal suspended 1400 Black</b></p> <p><b>4280lm 3000K Ra&gt;80 DALI-2 / Push</b></p> <p><b>Dim</b></p> <p><b>37W LED</b></p> <p>116 lm/W SDCM:3</p> <p>L80/B10&gt;100,000, L93/&gt;50,000</p> <p>Direct/Indirect 50/50%,</p>	<p><b>Class I</b></p> <p><b>IP20</b></p> <p><b>IK08</b></p>	<p>DALI-2 / Push Dim</p>	<p>Suspended, Indoor</p> <p>1x2m wire kit w/ceiling bracket</p> <p>5-pole Winsta mini with 5x1,5mm2 through wiring</p>	<p>L1401 x W42 x H70</p>
 <p>8246094720</p> <p><b>Lineal Corner Black 1740lm 3000K</b></p> <p><b>Ra&gt;80 DALI-2 / Push Dim</b></p> <p><b>17W LED</b></p> <p>102 lm/W SDCM:3</p> <p>L80/B10&gt;100,000, L93/&gt;50,000</p> <p>Direct,</p>	<p><b>Class I</b></p> <p><b>IP20</b></p> <p><b>IK08</b></p>	<p>DALI-2 / Push Dim</p>	<p>Suspended, Indoor</p> <p>1x2m wire kit w/ceiling bracket</p> <p>5-pole Winsta mini with 5x1,5mm2 through wiring</p>	<p>L642 x W42 x H70 x D571</p>
 <p>8246094665</p> <p><b>Lineal suspended 840 White</b></p> <p><b>2520lm 3000K Ra&gt;80 DALI-2 / Push</b></p> <p><b>Dim</b></p> <p><b>21W LED</b></p> <p>120 lm/W SDCM:3</p> <p>L80/B10&gt;100,000, L93/&gt;50,000</p> <p>Direct/Indirect 50/50%,</p>	<p><b>Class I</b></p> <p><b>IP20</b></p> <p><b>IK08</b></p>	<p>DALI-2 / Push Dim</p>	<p>Suspended, Indoor</p> <p>1x2m wire kit w/ceiling bracket</p> <p>5-pole Winsta mini with 5x1,5mm2 through wiring</p>	<p>L841 x W42 x H70</p>
 <p>8246094681</p> <p><b>Lineal suspended 1120 White</b></p> <p><b>3590lm 3000K Ra&gt;80 DALI-2 / Push</b></p> <p><b>Dim</b></p> <p><b>29W LED</b></p> <p>124 lm/W SDCM:3</p>	<p><b>Class I</b></p> <p><b>IP20</b></p> <p><b>IK08</b></p>	<p>DALI-2 / Push Dim</p>	<p>Suspended, Indoor</p> <p>1x2m wire kit w/ceiling bracket</p> <p>5-pole Winsta mini with 5x1,5mm2 through wiring</p>	<p>L1121 x W42 x H70</p>

# Article codes



Article	L80/B10>100,000, L93/>50,000	Protection	Control gear	Mounting/Connection	Dimensions
 Direct/Indirect 50/50% 8246094704	<b>Lineal suspended 1400 White</b> <b>4640lm 3000K Ra&gt;80 DALI-2 / Push Dim</b> <b>37W LED</b> 125 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct/Indirect 50/50%,	<b>Class I</b> <b>IP20</b> <b>IK08</b>	DALI-2 / Push Dim	Suspended, Indoor 1x2m wire kit w/ceiling bracket 5-pole Winsta mini with 5x1,5mm2 through wiring	L1401 x W42 x H70
 8246094746	<b>Lineal Corner White 1870lm 3000K</b> <b>Ra&gt;80 DALI-2 / Push Dim</b> <b>17W LED</b> 110 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct,	<b>Class I</b> <b>IP20</b> <b>IK08</b>	DALI-2 / Push Dim	Suspended, Indoor 1x2m wire kit w/ceiling bracket 5-pole Winsta mini with 5x1,5mm2 through wiring	L642 x W42 x H70 x D571
 8246094859	<b>Lineal suspended 1400 Black</b> <b>4500lm 4000K Ra&gt;80 DALI Emergency 3 hours</b> <b>37W LED</b> 122 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct/Indirect 50/50%,	<b>Class I</b> <b>IP20</b>	DALI Emergency 3 hours	Suspended, Indoor 1x2m wire kit w/ceiling bracket 5-pole Winsta mini with 5x1,5mm2 through wiring	L1401 x W42 x H70
 8246094610	<b>Lineal suspended 840 Black</b> <b>2480lm 4000K Ra&gt;80 DALI-2 / Push Dim</b> <b>21W LED</b> 118 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct/Indirect 50/50%,	<b>Class I</b> <b>IP20</b> <b>IK08</b>	DALI-2 / Push Dim	Suspended, Indoor 1x2m wire kit w/ceiling bracket 5-pole Winsta mini with 5x1,5mm2 through wiring	L841 x W42 x H70
 8246094636	<b>Lineal suspended 1120 Black</b> <b>3470lm 4000K Ra&gt;80 DALI-2 / Push Dim</b> <b>29W LED</b> 120 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct/Indirect 50/50%,	<b>Class I</b> <b>IP20</b> <b>IK08</b>	DALI-2 / Push Dim	Suspended, Indoor 1x2m wire kit w/ceiling bracket 5-pole Winsta mini with 5x1,5mm2 through wiring	L1121 x W42 x H70
 8246094652	<b>Lineal suspended 1400 Black</b> <b>4500lm 4000K Ra&gt;80 DALI-2 / Push Dim</b> <b>37W LED</b> 122 lm/W SDCM:3	<b>Class I</b> <b>IP20</b> <b>IK08</b>	DALI-2 / Push Dim	Suspended, Indoor 1x2m wire kit w/ceiling bracket 5-pole Winsta mini with 5x1,5mm2 through wiring	L1401 x W42 x H70

# Article codes



Article	L80/B10>100,000, L93/>50,000	Protection	Control gear	Mounting/Connection	Dimensions
	8246094733 <b>Lineal Corner Black 1830lm 4000K Ra&gt;80 DALI-2 / Push Dim 17W LED</b> 108 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct,	<b>Class I</b> <b>IP20</b> <b>IK08</b>	DALI-2 / Push Dim	Suspended, Indoor 1x2m wire kit w/ceiling bracket 5-pole Winsta mini with 5x1,5mm2 through wiring	L642 x W42 x H70 x D571
	8246094856 <b>Lineal suspended 1400 White 4960lm 4000K Ra&gt;80 DALI Emergency 3 hours 37W LED</b> 134 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct/Indirect 50/50%,	<b>Class I</b> <b>IP20</b>	DALI Emergency 3 hours	Suspended, Indoor 1x2m wire kit w/ceiling bracket 5-pole Winsta mini with 5x1,5mm2 through wiring	L1401 x W42 x H70
	8246094678 <b>Lineal suspended 840 White 2690lm 4000K Ra&gt;80 DALI-2 / Push Dim 21W LED</b> 128 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct/Indirect 50/50%,	<b>Class I</b> <b>IP20</b> <b>IK08</b>	DALI-2 / Push Dim	Suspended, Indoor 1x2m wire kit w/ceiling bracket 5-pole Winsta mini with 5x1,5mm2 through wiring	L841 x W42 x H70
	8246094694 <b>Lineal suspended 1120 White 3830lm 4000K Ra&gt;80 DALI-2 / Push Dim 29W LED</b> 132 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct/Indirect 50/50%,	<b>Class I</b> <b>IP20</b> <b>IK08</b>	DALI-2 / Push Dim	Suspended, Indoor 1x2m wire kit w/ceiling bracket 5-pole Winsta mini with 5x1,5mm2 through wiring	L1121 x W42 x H70
	8246094717 <b>Lineal suspended 1400 White 4960lm 4000K Ra&gt;80 DALI-2 / Push Dim 37W LED</b> 134 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct/Indirect 50/50%,	<b>Class I</b> <b>IP20</b> <b>IK08</b>	DALI-2 / Push Dim	Suspended, Indoor 1x2m wire kit w/ceiling bracket 5-pole Winsta mini with 5x1,5mm2 through wiring	L1401 x W42 x H70
	8246094759 <b>Lineal Corner White 1970lm 4000K Ra&gt;80 DALI-2 / Push Dim 17W LED</b> 116 lm/W SDCM:3 L80/B10>100,000, L93/>50,000	<b>Class I</b> <b>IP20</b> <b>IK08</b>	DALI-2 / Push Dim	Suspended, Indoor 1x2m wire kit w/ceiling bracket 5-pole Winsta mini with 5x1,5mm2 through wiring	L642 x W42 x H70 x D571

# Article codes



Article	Direct,	Protection	Control gear	Mounting/Connection	Dimensions
	8246095965 <b>Lineal 1120 Black Blind profile</b> DALI-2 / Push Dim		DALI-2 / Push Dim	Surface, Indoor 5-pole Winsta mini with 5x1,5mm2 through wiring	L1121 x W42 x H70
	8246095952 <b>Lineal 1120 White Blind profile</b> DALI-2 / Push Dim		DALI-2 / Push Dim	Surface, Indoor 5-pole Winsta mini with 5x1,5mm2 through wiring	L1121 x W42 x H70
<b>Accessories</b>					
	212198 <b>Black T-carrier ceiling bracket</b>				L30 x W20 x H5
	8241000346 <b>Lineal Wall Start kit Black</b>				L265 x W265 x H70
	8241000348 <b>Lineal Wall Extension kit Black</b>				L115 x W93 x H64
	8241000354 <b>Lineal T-ceiling Start kit Black</b>				L285 x W240 x H28
	8241000356 <b>Lineal T-ceiling Extension kit Black</b>				L120 x W94 x H65
	8249044942 <b>Lineal suspended Start kit Black</b>				L140 x W140 x H55
	8249045080 <b>Lineal 2240 Black Blind profile Front</b>				L2240 x W38 x H4
	212255 <b>T-profil White Suspension Rail 600mm</b>				L596 x W35 x H17
	8241000344 <b>Lineal Wall Start kit White</b>				L265 x W265 x H70
	8241000347 <b>Lineal Wall Extension kit White</b>				L115 x W93 x H64

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 8241000353 <b>Lineal T-ceiling Start kit White</b>				L285 x W240 x H28
 8241000355 <b>Lineal T-ceiling Extension kit White</b>				L120 x W94 x H65
 8249044955 <b>Lineal suspended Start kit White</b>				L140 x W140 x H55
 8249045077 <b>Lineal 2240 White Blind profile Front</b>				L2240 x W38 x H4
 8249044968 <b>Lineal 2800 Opalprism Diffuser</b>				L2800 x W38 x H4
 8249044971 <b>Lineal 5600 Opalprism Diffuser</b>				L5600 x W38 x H4
 8249044984 <b>Lineal 8400 Opalprism Diffuser</b>				L8400 x W38 x H4
 8249045116 <b>Lineal Wire kit 1 x 2m</b>				

• = This article is produced by order, with an expected delivery time of 3-4 weeks.