## Linus LED





Linus is an energy-efficient wall luminaire that is particularly well suited to optimal lighting in corridors and similar. Improved visual comfort is achieved through prismatic optics, prismatic optics ensure optimal light control, the optics have a markedly higher operating efficiency compared to a T5 solution. Cost-saving – no light source changes. Maintenance-friendly luminaire design. Also available with Tunable White.

## Linus LED



## **Product- and environment images**





## Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	8246078762 Linus LED White 1810lm 3000K Ra>80 DALI-2 / Push Dim 14W LED 129 lm/W SDCM:3 L90/B10>70,000, L94>50,000 Direct/Indirect 97/3%, Lens C, prismatic Conical	Class I IP20	DALI-2 / Push Dim	Surface, Indoor Screwless terminal block	L1170 x W123 x H90
	8246078759  Linus LED White 1810lm 3000K  Ra>80 On/Off  14W LED  129 Im/W SDCM:3  L90/B10>70,000, L94>50,000  Direct/Indirect 97/3%, Lens C, prismatic Conical	Class I IP20	On/Off	Surface, Indoor Screwless terminal block	L1170 x W123 x H90
	8246078788  Linus LED White 1890lm 4000K  Ra>80 DALI-2 / Push Dim  14W LED  135 Im/W SDCM:3  L90/B10>70,000, L94>50,000  Direct/Indirect 97/3%, Lens C, prismatic Conical	Class I IP20	DALI-2 / Push Dim	Surface, Indoor Screwless terminal block	L1170 x W123 x H90
	8246078775   Linus LED White 1890lm 4000K  Ra>80 On/Off  14W LED  135 lm/W SDCM:3  L90/B10>70,000, L94>50,000  Direct/Indirect 97/3%, Lens C, prismatic Conical	Class I IP20	On/Off	Surface, Indoor Screwless terminal block	L1170 x W123 x H90

<sup>• =</sup> This article is produced by order, with an expected delivery time of 3-4 weeks.