



Design: Christian Hvindt. Light for mounting on mast or wall lamp (680mm in diameter) is IP65-rated. Luminaire body, wall bracket and top made of die-cast aluminium, reflector and truncated cone made of polycarbonate. Powder-coated dark grey luminaire body, wall bracket and top. Reflector, inside of cone and top in special reflector-white colour. Reflector and optics are particularly well suited to giving a direct, direct/indirect, indirect or direct/asymmetrical light distribution via a clear or opal truncated cone. Complete with connection for operation of LED light sources mounted to component rail with connector system and pre-mounted with five-metre connection cable. Lamp head prepared for mounting on 60 mm or 108 mm mast. Electrical safety class II.

## Product- and environment images



# Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	8246079376 <b>Ray 680 D/I LED Grey 2990lm 3000K</b> <b>Ra&gt;80 On/Off</b> <b>24W LED</b> 125 lm/W SDCM:2 L90/B10>100,000 Direct/Indirect 85/15%, Opal	<b>Class I</b> <b>IP65</b> <b>IK10</b>	On/Off	Post - top (Ø60mm), Outdoor Cable 3x1mm <sup>2</sup> 5,0m	Ø680 x H703
	8246079389 <b>Ray 680 D/I LED Grey 2990lm 3000K</b> <b>Ra&gt;80 On/Off</b> <b>24W LED</b> 125 lm/W SDCM:2 L90/B10>100,000 Direct/Indirect 85/15%, Opal	<b>Class II</b> <b>IP65</b> <b>IK10</b>	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm <sup>2</sup> 5,0m	Ø680 x H703
	8246075260 <b>Ray 680 D/I LED Grey 2240lm 4000K</b> <b>Ra&gt;80 On/Off</b> <b>17W LED</b> 132 lm/W SDCM:2 L90/B10>100,000 Direct/Indirect 85/15%, Opal	<b>Class II</b> <b>IP65</b> <b>IK10</b>	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm <sup>2</sup> 5,0m	Ø680 x H703
<b>Accessories</b>					
	8249042083 • <b>Galvanized Pole 3m</b>				Ø60 x L3000
	8249042096 • <b>Galvanized Pole 4m</b>				Ø60 x L4000
	8249042106 • <b>Galvanized Conical Pole 3m</b>				Ø60 x L3000
	8249042119 • <b>Galvanized Conical Pole 4m</b>				Ø60 x L4000
	8249042122 • <b>Galvanized Pole 3m</b>				Ø60 x L3000
	8249042135 • <b>Galvanized Pole 4m</b>				Ø60 x L4000

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
	8249042180 • <b>Galvanized Ground anchor</b>			
	8249043943 • <b>Galvanized Reducer part from Ø76 to Ø60</b>			L230 x W98 x H230
	8249042148 • <b>Grey Design pole 3m</b>			Ø60 x L3000
	8249042151 • <b>Grey Design pole 4m</b>			Ø60 x L4000
	8249042164 <b>Grey Conical Pole 3m</b>			
	8249042177 • <b>Grey Conical Pole 4m</b>			Ø60 x L4000
	8249042999 <b>Ray 680 Design Cone Grey</b>			Ø108 x L100
	8249042203 • <b>Mounting unit</b>			
	8249043192 • <b>Ray 680 D/I LED Diffuser foil</b>			

• = This article is produced by order, with an expected delivery time of 3-4 weeks.