

High5



Design: Christian Hvidt. Mast top-mounted LED luminaire. IP66. LED luminaire. Base and top made of die-cast aluminium, front made of tempered glass. Base and diffuser in textured light grey. Direct lens optical solutions (Multilens). Complete with LED driver for operation of LED light sources mounted to component rail with internal connector/lampholder and pre-mounted with six-metre connection cable. Prepared for mounting on 60 mm mast. Safety class II.

High5



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>8246087863 High5 Grey Lens 1 2730lm 4000K Ra>70 On/Off 23W LED 119 lm/W SDCM:3 L80/B10>80,000 Lens 1, Lens</p>	Class II IP66 IK08	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L430 x W175 x H200
 <p>8246087931 High5 Grey Lens 2 2960lm 4000K Ra>70 On/Off 23W LED 129 lm/W SDCM:3 L90/B10>100,000, L98/B50>50,000 Lens 2,</p>	Class II IP66 IK08	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L430 x W175 x H200
Accessories				
 <p>8249042083 • Galvanized Pole 3m</p>				Ø60 x L3000
 <p>8249042096 • Galvanized Pole 4m</p>				Ø60 x L4000
 <p>8249042106 • Galvanized Conical Pole 3m</p>				Ø60 x L3000
 <p>8249042119 • Galvanized Conical Pole 4m</p>				Ø60 x L4000
 <p>8249042180 • Galvanized Ground anchor</p>				
 <p>8249043943 • Galvanized Reducer part from Ø76 to Ø60</p>				L230 x W98 x H230
 <p>8249043862 • Grey Design pole 3m</p>				
 <p>8249043891 • Grey Design pole 4m</p>				

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 8249042203 [•] Mounting unit				

[•] = This article is produced by order, with an expected delivery time of 3-4 weeks.