

High5



Design: Christian Hvidt. Mast top-mounted LED luminaire. IP66. LED luminaire. Base and top made of die-cast aluminium, front made of tempered glass. Base and diffuser in textured light grey. Direct lens optical solutions (Multilens). Complete with LED driver for operation of LED light sources mounted to component rail with internal connector/lampholder and pre-mounted with six-metre connection cable. Prepared for mounting on 60 mm mast. Safety class II.

High5













Product- and environment images



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	8246087863	Class II	On/Off	Post - top (Ø60mm), Outdoor	L430 x W175 x H200
	High5 Grey Lens 1 2730lm 4000K	IP66		Cable 2x1mm ² 6m	
	Ra>70 On/Off	IK08			
	23W LED				
	119 lm/W SDCM:3 L80/B10>80,000 Lens 1, Lens				
	8246087931	Class II	On/Off	Post - top (Ø60mm), Outdoor	L430 x W175 x H200
	High5 Grey Lens 2 2960lm 4000K	IP66		Cable 2x1mm ² 6m	
	Ra>70 On/Off	IK08			
	23W LED				
	129 lm/W SDCM:3 L90/B10>100,000, L98/B50>50,000 Lens 2,				
Accessories					
	8249042083				
	Galvanized Pole 3m				
	8249042096				
	Galvanized Pole 4m				
	8249042106				
	Galvanized Conical Pole 3m				
	8249042119				
	Galvanized Conical Pole 4m				
	8249042180				
	Galvanized Ground anchor				
	8249043943				L230 x W98 x H230
	Galvanized Reducer part from Ø76 to Ø60				
	8249043862				
	Grey Design pole 3m				
	8249043891				
	Grey Design pole 4m				



Article	Protection	Control gear	Mounting/Connection	Dimensions
 8249042203 Mounting unit				

= This article is produced by order, with an expected delivery time of 3-4 weeks.