



Design: Christian Hvidt. Mast or wall-mounted (600 mm diameter) IP66 LED luminaire. Base and top made of die-cast aluminium, inner diffuser made of PMMA opal and outer optics made of polycarbonate (PC). Grey or black base and top. Complete with LED driver for operation of LED light sources mounted to component rail with internal connector/lampholder and pre-mounted with five-metre connection cable. Prepared for mounting on 60 mm or designer mast. Safety class II.

Place



Product- and environment images



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	8246090627 Place Black 2410lm 3000K Ra>80 DYNADIM 21W LED 115 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct,	Class II IP66 IK10	DYNADIM	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	Ø600 x H291
	8246090630 Place Black 2410lm 3000K Ra>80 On/Off 21W LED 115 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct,	Class II IP66 IK10	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	Ø600 x H291
	8246088215 Place Grey 2410lm 3000K Ra>80 DYNADIM 21W LED 115 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct,	Class II IP66 IK10	DYNADIM	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	Ø600 x H291
	8246090892  Place Grey 2410lm 3000K Ra>80 Lumistep LS8 21W LED 115 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct,	Class II IP66 IK10	Lumistep LS8	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	Ø600 x H291
	8246087999 Place Grey 2410lm 3000K Ra>80 On/Off 21W LED 115 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct,	Class II IP66 IK10	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	Ø600 x H291
	8246090614 Place Black 2510lm 4000K Ra>80 DYNADIM 28W LED 90 lm/W SDCM:3 L90/B10>50,000, L70/B10>100,000 Direct,	Class II IP66 IK10	DYNADIM	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	Ø600 x H291

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	8246090643 Place Black 2530lm 4000K Ra>80 On/Off 21W LED 120 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct,	Class II IP66 IK10	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	Ø600 x H291
	8246088228 Place Grey 2530lm 4000K Ra>80 DYNADIM 21W LED 120 lm/W SDCM:3 L90/B10>50,000, L70/B10>100,000 Direct,	Class II IP66 IK10	DYNADIM	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	Ø600 x H291
	8246090902 • Place Grey 2530lm 4000K Ra>80 Lumistep LS8 21W LED 120 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct,	Class II IP66 IK10	Lumistep LS8	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	Ø600 x H291
	8246087407 Place Grey 2530lm 4000K Ra>80 On/Off 21W LED 120 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct,	Class II IP66 IK10	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	Ø600 x H291
Accessories					
	8249044492 Place Black Wall arm				L350 x W175 x H150
	8249042083 • Galvanized Pole 3m				Ø60 x L3000
	8249042096 • Galvanized Pole 4m				Ø60 x L4000
	8249042106 • Galvanized Conical Pole 3m				Ø60 x L3000

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 8249042119 • Galvanized Conical Pole 4m				Ø60 x L4000
 8249043888 • Galvanized Conical Pole 3m				
 8249043914 Galvanized Conical Pole 4m				
 8249043943 • Galvanized Reducer part from Ø76 to Ø60				L230 x W98 x H230
 8249043862 • Grey Design pole 3m				
 8249043875 • Grey Design pole 3m				
 8249043891 • Grey Design pole 4m				
 8249043901 • Grey Design pole 4m				
 8249044489 Place Grey Wall arm				L350 x W175 x H150
 8249042203 • Mounting unit				

• = This article is produced by order, with an expected delivery time of 3-4 weeks.