













Design: Christian Hvidt. . Light for mounting on mast or wall lamp (460 mm or 680 mm in diameter) is IP65-rated. Luminaire body, wall bracket and top made of die-cast aluminium, reflector and truncated cone made of polycarbonate. Powder-coated dark grey luminaire body, wall bracket and top. Reflector, inside of cone and top in special reflector-white colour. Reflector and optics are particularly well suited to giving a direct, direct/indirect, indirect or direct/asymmetrical light distribution via a clear or opal truncated cone. Complete with connection for operation of LED light sources mounted to component rail with connector system and pre-mounted with five-metre connection cable. Lamp head prepared for mounting on 60 mm or 108 mm mast (76 mm on request). Electrical safety class I or II. Ø460.

Product- and environment images










Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	8246088008 •	Class II	On/Off	Post - top (Ø60mm), Outdoor	Ø460 x H703
	Ray D LED Grey 2710lm 3000K Ra>80 On/Off 26W LED 104 lm/W SDCM:3 L80/B10>70,000, L90/B50>50,000 Direct,	IP65 IK10		Cable 2x1mm² 5,0m	
	8246087410 •	Class II	On/Off	Post - top (Ø60mm), Outdoor	Ø460 x H703
	Ray D LED Grey 2830lm 4000K Ra>80 On/Off 26W LED 109 lm/W SDCM:3 L80/B10>70,000, L90/B50>50,000 Direct,	IP65 IK10		Cable 2x1mm² 5,0m	
Accessories					
	8249042083 •				
	Galvanized Pole 3m				
	8249042096 •				
	Galvanized Pole 4m				
	8249042106 •				
	Galvanized Conical Pole 3m				
	8249042119 •				
	Galvanized Conical Pole 4m				
	8249042122 •				
	Galvanized Pole 3m				
	8249042135 •				
	Galvanized Pole 4m				
	8249042180 •				
	Galvanized Ground anchor				
	8249043943 •				
	Galvanized Reducer part from Ø76 to Ø60				L230 x W98 x H230

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 8249042148 • Grey Design pole 3m				
 8249042151 • Grey Design pole 4m				
 8249042164 Grey Conical Pole 3m				
 8249042177 • Grey Conical Pole 4m				
 8249042999 Ray 680 Design Cone Grey Design cone				Ø108 x L100
 8249042203 • Mounting unit				
 8249043192 • Ray 680 D/I LED Diffuser foil				

• = This article is produced by order, with an expected delivery time of 3-4 weeks.