

# CircLED Bollard



Design: Christian Hvidt. . Attractive, vandal-resistant LED bollard designed for use in public places, parks, paths, etc. CircLED combines energy saving with indirect light distribution, which gives comfortable and pleasant lighting without light pollution. IK10, IP65, KL II. Design: Christian Hvidt

# CircLED Bollard










## Product- and environment images



# Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	8246079347 <span style="color: orange;">•</span> <b>CircLED Bollard Black 650lm 3000K Ra 98 On/Off 16W LED</b> 41 lm/W SDCM:2 L80/B10>100,000 Indirect, Reflector	<b>Class II</b> <b>IP65</b> <b>IK10</b>	On/Off	Onto surfaces or ground anchor, Outdoor	Ø220 x H900
	8246087067 <b>CircLED Bollard Black Soft 740lm 3000K Ra 98 On/Off 16W LED</b> 46 lm/W SDCM:2 L80/B10>100,000 Indirect,	<b>Class II</b> <b>IP65</b> <b>IK09</b>	On/Off	Onto surfaces or ground anchor, Outdoor	Ø220 x H900
	8246096032 <b>CircLED Bollard Grey Soft 740lm 3000K Ra 98 On/Off 16W LED</b> 46 lm/W SDCM:2 L80/B10>100,000 Indirect,	<b>Class II</b> <b>IP65</b> <b>IK09</b>	On/Off	Onto surfaces or ground anchor, Outdoor	Ø220 x H900
	8246093857 <b>CircLED Bollard Black Soft 770lm 4000K Ra 98 On/Off 16W LED</b> 48 lm/W SDCM:2 L80/B10>100,000 Indirect,	<b>Class II</b> <b>IP65</b> <b>IK09</b>	On/Off	Onto surfaces or ground anchor, Outdoor	Ø220 x H900
	8246096045 <b>CircLED Bollard Grey Soft 770lm 4000K Ra 98 On/Off 16W LED</b> 48 lm/W SDCM:2 L80/B10>100,000 Indirect,	<b>Class II</b> <b>IP65</b> <b>IK09</b>	On/Off	Onto surfaces or ground anchor, Outdoor	Ø220 x H900
<b>Accessories</b>					
	8249042067 <b>Ground anchor</b>				Ø155 x L248 x W108 x H450
	8249042070 <b>Ground anchor f/'Cetong"</b>				Ø155 x H450

• = This article is produced by order, with an expected delivery time of 3-4 weeks.