

CircLED Bollard



Attractive, vandal-resistant LED bollard designed for use in public places, parks, paths, etc. CircLED combines energy saving with indirect light distribution, which gives comfortable and pleasant lighting without light pollution. Design: Christian Hvidt

CircLED Bollard



Product- and environment images



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>8246079347 • CircLED Bollard Black 650lm 3000K Ra 98 On/Off 16W LED 41 lm/W SDCM:2 L80/B10>100,000 Indirect, Reflector</p>	<p>Class II IP65 IK10</p>	On/Off	Onto surfaces or ground anchor, Outdoor	Ø220 x H900
 <p>8246087067 CircLED Bollard Black Soft 740lm 3000K Ra 98 On/Off 16W LED 46 lm/W SDCM:2 L80/B10>100,000 Indirect,</p>	<p>Class II IP65 IK09</p>	On/Off	Onto surfaces or ground anchor, Outdoor	Ø220 x H900
 <p>8246096032 CircLED Bollard Grey Soft 740lm 3000K Ra 98 On/Off 16W LED 46 lm/W SDCM:2 L80/B10>100,000 Indirect,</p>	<p>Class II IP65 IK09</p>	On/Off	Onto surfaces or ground anchor, Outdoor	Ø220 x H900
 <p>8246093857 CircLED Bollard Black Soft 770lm 4000K Ra 98 On/Off 16W LED 48 lm/W SDCM:2 L80/B10>100,000 Indirect,</p>	<p>Class II IP65 IK09</p>	On/Off	Onto surfaces or ground anchor, Outdoor	Ø220 x H900
 <p>8246096045 CircLED Bollard Grey Soft 770lm 4000K Ra 98 On/Off 16W LED 48 lm/W SDCM:2 L80/B10>100,000 Indirect,</p>	<p>Class II IP65 IK09</p>	On/Off	Onto surfaces or ground anchor, Outdoor	Ø220 x H900
Accessories				
 <p>8249042067 Ground anchor</p>				Ø155 x L248 x W108 x H450
 <p>8249042070 Ground anchor f/'Cetong"</p>				Ø155 x H450

• = This article is produced by order, with an expected delivery time of 3-4 weeks.