

CircLED Single



Design: Christian Hvidt. Light for mounting on mast, IP65-rated. Luminaire body made of die-cast aluminium, powder-coated in black or grey. Reflector made of aluminium, powder-coated white. Optics are particularly well suited to giving a direct light distribution due to the tempered glass front. Complete with LED driver for operation of LED light sources mounted to component rail pre-mounted with six-metre connection cable. Lamp head prepared for mounting at 60 mm. Electrical rating class II. IK09. CircLED is based on the latest LED technology and optics for a long-lasting solution for streets and small roads, public areas and paths. CircLED is available as a single lens or a multi-lens version. Both combine energy savings, durability and precise light distribution and are optimal solutions for retrofitting of old mercury or sodium lamps.

CircLED Single



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>8246084471 ● CircLED Single Top Black 1640lm 4000K Ra>80 On/Off 14W LED 117 lm/W SDCM:2 L90/B10>100,000 Single Lens, Lens</p>	Class II IP66 IK09	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185
 <p>8246084497 ● CircLED Single Top Black 2430lm 4000K Ra>80 On/Off 21W LED 116 lm/W SDCM:2 L90/B10>100,000 Single Lens, Lens</p>	Class II IP66 IK09	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185
 <p>8246084510 ● CircLED Single Top Black 3320lm 4000K Ra>80 On/Off 30W LED 111 lm/W SDCM:2 L90/B10>100,000 Single Lens, Lens</p>	Class II IP66 IK09	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185
 <p>8246086165 ● CircLED Single Side Black 3320lm 4000K Ra>80 On/Off 30W LED 111 lm/W SDCM:2 L90/B10>100,000 Single Lens, Lens</p>	Class II IP66 IK09	On/Off	Pole - Side (Ø48mm), Outdoor Cable 2x1mm ² 10m	L523 x W390 x H135
 <p>8246086518 ● CircLED Single Grey 1640lm 4000K Ra>80 DYNADIM Profil 1 14W LED 117 lm/W SDCM:2 L90/B10>100,000 Single Lens, Lens</p>	Class II IP66 IK09	DYNADIM Profil 1	Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185
 <p>8246086521 ● CircLED Single Grey 2430lm 4000K Ra>80 DYNADIM Profil 1 21W LED 116 lm/W SDCM:2 L90/B10>100,000 Single Lens, Lens</p>	Class II IP66 IK09	DYNADIM Profil 1	Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>8246086534 ● CircLED Single Top Adjustable 5-17° Grey 1640lm 4000K Ra>80 DYNADIM Profil 1 14W LED 117 lm/W SDCM:2 L90/B10>100,000 Single Lens, Lens</p>	Class II IP66 IK09	DYNADIM Profil 1	Post - adjustable head 5-17°, Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185
 <p>8246086547 ● CircLED Single Top Adjustable 5-17° Grey 2430lm 4000K Ra>80 DYNADIM Profil 1 21W LED 116 lm/W SDCM:2 L90/B10>100,000 Single Lens, Lens</p>	Class II IP66 IK09	DYNADIM Profil 1	Post - adjustable head 5-17°, Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185
 <p>8246084455 ● CircLED Single Top Grey 1640lm 4000K Ra>80 On/Off 14W LED 117 lm/W SDCM:2 L90/B10>100,000 Single Lens, Lens</p>	Class II IP66 IK09	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185
 <p>8246084468 ● CircLED Single Top Adjustable 5-17° Grey 1640lm 4000K Ra>80 On/Off 14W LED 117 lm/W SDCM:2 L90/B10>100,000 Single Lens, Lens</p>	Class II IP66 IK09	On/Off	Post - adjustable head 5-17°, Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185
 <p>8246084484 ● CircLED Single Top Grey 2430lm 4000K Ra>80 On/Off 21W LED 116 lm/W SDCM:2 L90/B10>100,000 Single Lens, Lens</p>	Class II IP66 IK09	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185
 <p>8246084507 ● CircLED Single Top Grey 3320lm 4000K Ra>80 On/Off 30W LED 111 lm/W SDCM:2 L90/B10>100,000</p>	Class II IP66 IK09	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185

Article codes



Article	Single Lens, Lens	Protection	Control gear	Mounting/Connection	Dimensions
	8246086178 • CircLED Single Side Grey 3320lm 4000K Ra>80 On/Off 30W LED 111 lm/W SDCM:2 L90/B10>100,000 Single Lens, Lens	Class II IP66 IK09	On/Off	Pole - Side (Ø48mm), Outdoor Cable 2x1mm ² 10m	L523 x W390 x H135
	8246086369 • CircLED Single Top Adjustable 5-17° Grey 2430lm 4000K Ra>80 On/Off 21W LED 116 lm/W SDCM:2 L90/B10>100,000 Single Lens, Lens	Class II IP66 IK09	On/Off	Post - adjustable head 5-17°, Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185
	8246086372 • CircLED Single Top Adjustable 5-17° Grey 3320lm 4000K Ra>80 On/Off 30W LED 111 lm/W SDCM:2 L90/B10>100,000 Single Lens, Lens	Class II IP66 IK09	On/Off	Post - adjustable head 5-17°, Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185
	8246089337 • CircLED Single Top Grey 2170lm 4000K Ra>80 On/Off 21W LED 103 lm/W SDCM:2 L90/B10>100,000 Single Lens, Lens	Class I IP66 IK09	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185
	8246082774 • CircLED Single Top Adjustable 5-17° 1640lm 4000K Ra>80 On/Off 14W LED 117 lm/W SDCM:2 L90/B10>100,000 Single Lens, Lens	Class I IP66 IK09	On/Off	Post - adjustable head 5-17°, Outdoor Cable 3x1mm ² 6,0m	L460 x W390 x H185
Accessories					
	8249042083 • Galvanized Pole 3m				Ø60 x L3000

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 8249042096 • Galvanized Pole 4m				Ø60 x L4000
 8249042106 • Galvanized Conical Pole 3m				Ø60 x L3000
 8249042119 • Galvanized Conical Pole 4m				Ø60 x L4000
 8249042180 • Galvanized Ground anchor				
 8249043927 CircLED Single Galvanized Side arm - 2 arms				
 8249043930 CircLED Single Galvanized Side arm - 1 arm				
 8249043943 • Galvanized Reducer part from Ø76 to Ø60				L230 x W98 x H230
 8249043862 • Grey Design pole 3m				
 8249043891 • Grey Design pole 4m				
 8249042203 • Mounting unit				

• = This article is produced by order, with an expected delivery time of 3-4 weeks.