

CircLED Multi



Design: Christian Hvidt. Light for mounting on mast, IP66-rated. Luminaire body made of die-cast aluminium, powder-coated in black or grey. Reflector made of aluminium, powder-coated white. Optics are particularly well suited to giving a direct light distribution due to the tempered glass front. Complete with LED driver for operation of LED light sources mounted to component rail pre-mounted with six-metre connection cable. Lamp head prepared for mounting on 60 mm mast. Electrical safety class I or II. IK09. Design: Christian Hvidt

CircLED Multi



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>8246084565 • CircLED Multi Top Black Lens 2, Class II 3120lm 4000K Ra>70 On/Off 23W LED 136 lm/W SDCM:3 L80/B10>100,000 Multi Lens, Lens</p>	Class II IP66 IK09	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185
 <p>8246086437 • CircLED Multi Top Grey Lens 2, Class II 2520lm 4000K Ra>70 DYNADIM Profil 1 19W LED 133 lm/W SDCM:3 L80/B10>100,000 Multi Lens, Lens</p>	Class II IP66 IK09	DYNADIM Profil 1	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185
 <p>8246086440 • CircLED Multi Top Grey Lens 2, Class II 3120lm 4000K Ra>70 DYNADIM Profil 1 23W LED 136 lm/W SDCM:3 L80/B10>100,000 Multi Lens, Lens</p>	Class II IP66 IK09	DYNADIM Profil 1	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185
 <p>8246086453 • CircLED Multi Top Grey Lens 2, Class II 3950lm 4000K Ra>70 DYNADIM Profil 1 31W LED 127 lm/W SDCM:3 L80/B10>100,000 Multi Lens, Lens</p>	Class II IP66 IK09	DYNADIM Profil 1	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185
 <p>8246086479 • CircLED Multi Top Adjustable 5-17° Grey Lens 2, Class II 3120lm 4000K Ra>70 DYNADIM Profil 1 23W LED 136 lm/W SDCM:3 L80/B10>100,000 Multi Lens, Lens</p>	Class II IP66 IK09	DYNADIM Profil 1	Post - adjustable head 5-17°, Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>8246086482 • CircLED Multi Top Adjustable 5-17° Grey Lens 2, Class II 3950lm 4000K Ra>70 DYNADIM Profil 1 31W LED 127 lm/W SDCM:3 L80/B10>100,000 Multi Lens, Lens</p>	Class II IP66 IK09	DYNADIM Profil 1	Post - adjustable head 5-17°, Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185
 <p>8246086495 • CircLED Multi Side Grey Lens 2, Class II 3950lm 4000K Ra>70 DYNADIM Profil 1 31W LED 127 lm/W SDCM:3 L80/B10>100,000 Multi Lens, Lens</p>	Class II IP66 IK09	DYNADIM Profil 1	Pole - Side (Ø48mm), Outdoor Cable 2x1mm ² 10m	L523 x W390 x H135
 <p>8246090876 CircLED Multi Top Grey Lens 2, Class II 3120lm 4000K Ra>70 Lumistep LS8 23W LED 136 lm/W SDCM:3 L80/B10>100,000 Multi Lens, Lens</p>	Class II IP66 IK09	Lumistep LS8	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185
 <p>8246084523 CircLED Multi Top Grey Lens 2, Class II 2520lm 4000K Ra>70 On/Off 19W LED 133 lm/W SDCM:3 L80/B10>100,000 Multi Lens, Lens</p>	Class II IP66 IK09	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185
 <p>8246084536 • CircLED Multi Top Adjustable 5-17° Grey Lens 2, Class II 2520lm 4000K Ra>70 On/Off 19W LED 133 lm/W SDCM:3 L80/B10>100,000 Multi Lens, Lens</p>	Class II IP66 IK09	On/Off	Post - adjustable head 5-17°, Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>8246084552 CircLED Multi Top Grey Lens 2, Class II 3120lm 4000K Ra>70 On/Off 23W LED 136 lm/W SDCM:3 L80/B10>100,000 Multi Lens, Lens</p>	Class II IP66 IK09	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185
 <p>8246084578 CircLED Multi Top Grey Lens 2, Class II 3950lm 4000K Ra>70 On/Off 31W LED 127 lm/W SDCM:3 L80/B10>100,000 Multi Lens, Lens</p>	Class II IP66 IK09	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185
 <p>8246086398 CircLED Multi Top Adjustable 5-17° Grey Lens 2, Class II 3120lm 4000K Ra>70 On/Off 23W LED 136 lm/W SDCM:3 L80/B10>100,000 Multi Lens, Lens</p>	Class II IP66 IK09	On/Off	Post - adjustable head 5-17°, Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185
 <p>8246086408 CircLED Multi Top Adjustable 5-17° Grey Lens 2, Class II 3950lm 4000K Ra>70 On/Off 31W LED 127 lm/W SDCM:3 L80/B10>100,000 Multi Lens, Lens</p>	Class II IP66 IK09	On/Off	Post - adjustable head 5-17°, Outdoor Cable 2x1mm ² 6m	L460 x W390 x H185
 <p>8246086411 CircLED Multi Side Grey Lens 2, Class II 3950lm 4000K Ra>70 On/Off 31W LED 127 lm/W SDCM:3 L80/B10>100,000 Multi Lens, Lens</p>	Class II IP66 IK09	On/Off	Pole - Side (Ø48mm), Outdoor Cable 2x1mm ² 10m	L523 x W390 x H135
 <p>8246094115 CircLED Multi Top Grey Lens 3, Class II 9870lm 4000K Ra>70 On/Off 82W LED</p>	Class II IP66 IK09	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 10m	L460 x W390 x H185

Article codes



Article	120 lm/W SDCM:3	Protection	Control gear	Mounting/Connection	Dimensions
 L80/B10>80,000 Multi Lens, Lens II	8246094128 CircLED Multi Top Grey Lens 3, Class II 5820lm 4000K Ra>70 On/Off 42W LED	Class II IP66 IK09	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 10m	L460 x W390 x H185
	8246094157 CircLED Multi Side Grey Lens 3, Class II 9870lm 4000K Ra>70 On/Off 82W LED	Class II IP66 IK09	On/Off	Pole - Side (Ø48mm), Outdoor Cable 2x1mm ² 10m	L523 x W390 x H135
	8246094160 CircLED Multi Side Grey Lens 3, Class II 5820lm 4000K Ra>70 On/Off 42W LED	Class II IP66 IK09	On/Off	Pole - Side (Ø48mm), Outdoor Cable 2x1mm ² 10m	L523 x W390 x H135
	8246083045 • CircLED Multi Lens 2, Class I Top 3120lm 4000K Ra>70 On/Off 23W LED	Class I IP66 IK09	On/Off	Post - top (Ø60mm), Outdoor Cable 3x1mm ² 6,0m	L460 x W390 x H185
	8246083058 • CircLED Multi Lens 2, Class I Top 3950lm 4000K Ra>70 On/Off 31W LED	Class I IP66 IK09	On/Off	Post - top (Ø60mm), Outdoor Cable 3x1mm ² 6,0m	L460 x W390 x H185

Accessories

	8249042083 • Galvanized Pole 3m				Ø60 x L3000
---	---	--	--	--	-------------

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 8249042096 • Galvanized Pole 4m				Ø60 x L4000
 8249042106 • Galvanized Conical Pole 3m				Ø60 x L3000
 8249042119 • Galvanized Conical Pole 4m				Ø60 x L4000
 8249042180 • Galvanized Ground anchor				
 8249043927 CircLED Single Galvanized Side arm - 2 arms				
 8249043930 CircLED Single Galvanized Side arm - 1 arm				
 8249043943 • Galvanized Reducer part from Ø76 to Ø60				L230 x W98 x H230
 8249043862 • Grey Design pole 3m				
 8249043891 • Grey Design pole 4m				
 8249042203 • Mounting unit				

• = This article is produced by order, with an expected delivery time of 3-4 weeks.