



LED luminaire for wall mounting. Vandal resistant, versatile wall luminaire with a thin profile that suits most environments. An adjustable wall/corner attachment is available as an accessory, offering several creative solutions for lighting above doors, gates and pathways. Fevik is connectable from the top and has outlets on the back panel for external wiring from both above and below. A connector between the wall attachment and the luminaire means that mounting is quick and easy. The light source can be changed by a competent professional. IP65 and IK10.

Fevik








Product- and environment images



Article codes



| Article | Protection | Control gear | Mounting/Connection | Dimensions |
|---|--|--------------|--|--------------------|
|  <p>611226 Fevik 3000 White 2535lm 3000K Ra>80 Twilight 31W LED 82 lm/W SDCM:3 L70/B50>50,000 Beam: 100°, Direct, Glass Clear</p> | Class I IP44 IK10 | Twilight | Surface, Outdoor Screwless terminal block | W223 x H110 x D276 |
| Accessories | | | | |
|  <p>623247 Fevik Armmount Graphite</p> | | | | W130 x H130 x D240 |
|  <p>623248 Fevik Graphite Pole bracket</p> | | | | L225 x W105 x H111 |
|  <p>623249 Fevik Graphite Wall and corner bracket</p> | | | | W220 x H100 x D135 |
|  <p>600001 Number Plate 220x170mm</p> | | | Indoor / Outdoor | L220 x W170 x H10 |