

# Arco Air



Decorative LED lamp for wall and garden. Made of powder-coated corrosion-proof aluminium. Installed with dimmable, replaceable GU10 LED bulb (included) that illuminates a top reflector, thus giving soft light with a pleasant effect. Impact-resistant with IK08 and phenolic screw to prohibit access to the light source.

# Arco Air



## Product- and environment images



# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>623620  <b>Arco Air Graphite 75lm 2700K</b>  <b>Ra&gt;90 Trailing edge</b>  <b>6W LED</b>            13 lm/W SDCM:2            L70/B50&gt;50,000            Beam: 360°, Direct/Indirect, Glass            Clear</p>	<b>Class I</b> <b>IP54</b> <b>IK08</b>	Trailing edge	Pole, wall, bollard or earthing rod, Outdoor Screwless terminal block	Ø160 x H963
 <p>623621  <b>Arco Air Graphite R 75lm 2700K</b>  <b>Ra&gt;90 Trailing edge</b>  <b>6W LED</b>            13 lm/W SDCM:2            L70/B50&gt;50,000            Beam: 360°, Direct/Indirect, Glass            Clear</p>	<b>Class I</b> <b>IP54</b> <b>IK08</b>	Trailing edge	Pole, wall, bollard or earthing rod, Outdoor Screwless terminal block	Ø160 x H400
 <p>623622  <b>Arco Air Graphite Wall 75lm 2700K</b>  <b>Ra&gt;90 Trailing edge</b>  <b>6W LED</b>            13 lm/W SDCM:2            L70/B50&gt;50,000            Beam: 360°, Direct/Indirect, Glass            Clear</p>	<b>Class I</b> <b>IP54</b> <b>IK08</b>	Trailing edge	Surface, Outdoor Screwless terminal block	W160 x H356 x D219
 <p>623623  <b>Arco Air Graphite 100lm 3000K</b>  <b>Ra&gt;80 Trailing edge</b>  <b>6.2W LED</b>            16 lm/W SDCM:4            L70/B50&gt;25,000            Beam: 360°, Direct/Indirect, Glass            Clear</p>	<b>Class I</b> <b>IP54</b> <b>IK08</b>	Trailing edge	Pole, wall, bollard or earthing rod, Outdoor Screwless terminal block	Ø160 x H963
 <p>623624  <b>Arco Air Graphite R 100lm 3000K</b>  <b>Ra&gt;80 Trailing edge</b>  <b>6.2W LED</b>            16 lm/W SDCM:4            L70/B50&gt;25,000            Beam: 360°, Direct/Indirect, Glass            Clear</p>	<b>Class I</b> <b>IP54</b> <b>IK08</b>	Trailing edge	Pole, wall, bollard or earthing rod, Outdoor Screwless terminal block	Ø160 x H400
 <p>623625  <b>Arco Air Graphite Wall 100lm</b>  <b>3000K Ra&gt;80 Trailing edge</b>  <b>6.2W LED</b></p>	<b>Class I</b> <b>IP54</b> <b>IK08</b>	Trailing edge	Outdoor Screwless terminal block	W160 x H356 x D219
<b>Accessories</b>	16 lm/W SDCM:4			

# Article codes



Article	L70/B50>25,000	Protection	Control gear	Mounting/Connection	Dimensions
 A technical drawing showing a vertical beam with a mounting bracket attached to its side. The bracket has two vertical supports and a horizontal top bar.	Beam, 5°, Direct, Glass Clear 00581 <b>Arco Air Anchoring set</b>				Ø148 x H245