



IP66 luminaire for mounting on ceiling. Made of UV-stabilised polycarbonate. The slim design, unique one-hand closing mechanism at both ends, through wiring and option of looping ensures very quick and simple installation. Can be used in cold rooms with temperatures down to -25°C. 5-pole (On/Off) or 7-pole (DALI) terminal block with 5 x 2,5 mm².

Area 66



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 120003 Area 66 Grey 4500lm 4000K Ra>80 DALI-2 36W LED 125 lm/W SDCM:3 L80/B10>100,000, L90/B50>50,000 Beam: 100°, Direct, Opal	Class I IP66 IK10	DALI-2	Surface, Indoor 7-pole screwless terminal block with 5x2,5mm² (+DALI) through wiring	L1174 x W92 x H70
 120004 Area 66 Grey 5930lm 4000K Ra>80 DALI-2 46W LED 129 lm/W SDCM:3 L80/B10>100,000, L90/B50>50,000 Beam: 100°, Direct, Opal	Class I IP66 IK10	DALI-2	Surface, Indoor 7-pole screwless terminal block with 5x2,5mm² (+DALI) through wiring	L1460 x W92 x H70
 120001 Area 66 Grey 4500lm 4000K Ra>80 On/Off 36W LED 125 lm/W SDCM:3 L80/B10>100,000, L90/B50>50,000 Beam: 100°, Direct, Opal	Class I IP66 IK10	On/Off	Surface, Indoor 5-pole screwless terminal block with 5x2,5mm² through wiring	L1174 x W92 x H70
 120002 Area 66 Grey 5930lm 4000K Ra>80 On/Off 46W LED 129 lm/W SDCM:3 L80/B10>100,000, L90/B50>50,000 Beam: 100°, Direct, Opal	Class I IP66 IK10	On/Off	Surface, Indoor 5-pole screwless terminal block with 5x2,5mm² through wiring	L1460 x W92 x H70
Accessories				
 120006 45° Fastening				L42 x W42 x H15
 820259 Start current limiter DIN 16A				L90 x W18 x H58
 8249044900 Wirekit 2x5m				L19 x W25 x H150
 8249044913 Mounting kit for adjustable angulation				L100 x W98 x H95