



Attractive, square LED wall luminaire that can be installed both indoors and outdoors. Made of die-cast powder-coated aluminium. Diffuser made of UV-stabilised opalescent polycarbonate, two inputs/outputs for cables, option of both visible and hidden cabling, and loopable terminal block. IP65 and vandal-resistant rating IK10.

Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>614189 • Bassi Black 690lm 3000K Ra>80 Sensor 11W LED 63 lm/W SDCM:3 L70/B50>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H80
 <p>614187 Bassi Black 690lm 3000K Ra>80 Trailing edge 10W LED 69 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H80
 <p>614188 Bassi Black 690lm 3000K Ra>80 Twilight 10W LED 69 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Twilight	Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H80
 <p>623189 • Bassi Graphite 690lm 3000K Ra>80 Sensor 11W LED 63 lm/W SDCM:3 L70/B50>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H80
 <p>623187 Bassi Graphite 690lm 3000K Ra>80 Trailing edge 10W LED 69 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H80
 <p>623188 Bassi Graphite 690lm 3000K Ra>80 Twilight 10W LED 69 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Twilight	Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H80

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	611189 Bassi White 690lm 3000K Ra>80 Sensor 11W LED 63 lm/W SDCM:3 L70/B50>50,000 Beam: 120°, Direct, Opal	Class II IP65 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H80
	614180 Bassi Black E27 Beam: 120°, Direct, Opal	Class II IP65 IK10		Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H90
	623180 Bassi Graphite E27 Beam: 120°, Direct, Opal	Class II IP65 IK10		Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H90
	611180 Bassi White E27 Beam: 120°, Direct, Opal	Class II IP65 IK10		Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H90

Accessories

- = This article is produced by order, with an expected delivery time of 3-4 weeks.