



Attractive, square LED wall luminaire that can be installed both indoors and outdoors. Made of die-cast powder-coated aluminium. Diffuser made of UV-stabilised opalescent polycarbonate, two inputs/outputs for cables, option of both visible and hidden cabling, and loopable terminal block. IP65 and vandal-resistant rating IK10.

Basso









Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>624194 Basso 2000 Black 1550lm 3000K Ra>80 Sensor 14W LED 111 lm/W SDCM:3 L70/B50>100,000 Beam: 120°, Direct, Opal</p>	Class I IP65 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	L308 x W308 x H88
 <p>614194 Basso 2000 Black 1550lm 3000K Ra>80 Trailing edge 14W LED 111 lm/W SDCM:3 L70/B50>100,000 Beam: 120°, Direct, Opal</p>	Class I IP65 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L308 x W308 x H88
 <p>633194 Basso 2000 Graphite 1550lm 3000K Ra>80 Sensor 14W LED 111 lm/W SDCM:3 L70/B50>100,000 Beam: 120°, Direct, Opal</p>	Class I IP65 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	L308 x W308 x H88
 <p>633196 Basso 3000 Graphite 2440lm 3000K Ra>80 Sensor 22W LED 111 lm/W SDCM:3 L70/B50>50,000 Beam: 120°, Direct, Opal</p>	Class I IP65 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	L308 x W308 x H88
 <p>623194 Basso 2000 Graphite 1550lm 3000K Ra>80 Trailing edge 14W LED 111 lm/W SDCM:3 L70/B50>100,000 Beam: 120°, Direct, Opal</p>	Class I IP65 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L308 x W308 x H88
 <p>621194 Basso 2000 White 1570lm 3000K Ra>80 Sensor 14W LED 112 lm/W SDCM:3 L70/B50>100,000 Beam: 120°, Direct, Opal</p>	Class I IP65 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	L308 x W308 x H88

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	611194 Basso 2000 White 1570lm 3000K Ra>80 Trailing edge 14W LED 112 lm/W SDCM:3 L70/B50>100,000 Beam: 120°, Direct, Opal	Class I IP65 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L308 x W308 x H88

Accessories