



LED luminaire for walls and ceiling for both outdoor and indoor use. Made of die-cast powder-coated aluminium, glass diffuser. 33 cm in total height, Class II means that it can be mounted without earthing, direct 230 V with loopable terminal block.

Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 914012 Callisto Black 190lm 2700K Ra>80 Trailing edge 3W LED 63 lm/W SDCM:3 L70/B50>50,000 Beam: 65°, Direct, Glass Clear	Class II IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø110 x H33
 923012 Callisto Graphite 190lm 2700K Ra>80 Trailing edge 3W LED 63 lm/W SDCM:3 L70/B50>50,000 Beam: 65°, Direct, Glass Clear	Class II IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø110 x H33
 912012 Callisto White 200lm 2700K Ra>80 Trailing edge 3W LED 67 lm/W SDCM:3 L70/B50>50,000 Beam: 65°, Direct, Glass Clear	Class II IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø110 x H33
 914010 Callisto Black 200lm 3000K Ra>80 Trailing edge 3W LED 67 lm/W SDCM:3 L70/B50>50,000 Beam: 65°, Direct, Glass Clear	Class II IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø110 x H33
 923010 Callisto Graphite 200lm 3000K Ra>80 Trailing edge 3W LED 67 lm/W SDCM:3 L70/B50>50,000 Beam: 65°, Direct, Glass Clear	Class II IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø110 x H33
 912010 Callisto White 210lm 3000K Ra>80 Trailing edge 3W LED 70 lm/W SDCM:3 L70/B50>50,000 Beam: 65°, Direct, Glass Clear	Class II IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø110 x H33



Article		Protection	Control gear	Mounting/Connection	Dimensions
	914013	Class II	Trailing edge	Surface, Indoor / Outdoor	Ø110 x H33
	Callisto Black 200lm 4000K Ra>80	IP65		Screwless terminal block	
	Trailing edge	IK06			
	3W LED				
	67 lm/W SDCM:3				
	L70/B50>50,000				
	Beam: 65°, Direct, Glass Clear				