

Callisto Wall



Good little LED luminaire for walls and ceiling. For both outdoor and indoor use. Well integrated LED chip, dimmable via phase-dimming. Made of die-cast powder-coated aluminium, glass diffuser. 33 cm in total height, KL II means that it can be mounted without earthing, direct 230 V with loopable quick clips.

Callisto Wall



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 914017 Callisto Wall Black 100lm 2700K Ra>80 Trailing edge 3W LED 33 lm/W SDCM:3 L70/B50>50,000 Beam: 70°/40°, Direct/Asymmetric, Glass Clear	Class II IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø110 x H35
 923017 Callisto Wall Graphite 100lm 2700K Ra>80 Trailing edge 3W LED 33 lm/W SDCM:3 L70/B50>50,000 Beam: 70°/40°, Direct/Asymmetric, Glass Clear	Class II IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø110 x H35
 912017 Callisto Wall White 110lm 2700K Ra>80 Trailing edge 3W LED 37 lm/W SDCM:3 L70/B50>50,000 Beam: 70°/40°, Direct/Asymmetric, Glass Clear	Class II IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø110 x H35
 914015 Callisto Wall Black 110lm 3000K Ra>80 Trailing edge 3W LED 37 lm/W SDCM:3 L70/B50>50,000 Beam: 70°/40°, Direct/Asymmetric, Glass Clear	Class II IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø110 x H35
 923015 Callisto Wall Graphite 110lm 3000K Ra>80 Trailing edge 3W LED 37 lm/W SDCM:3 L70/B50>50,000 Beam: 70°/40°, Direct/Asymmetric, Glass Clear	Class II IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø110 x H35
 912015 Callisto Wall White 120lm 3000K Ra>80 Trailing edge 3W LED 40 lm/W SDCM:3	Class II IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø110 x H35

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	L70/B50>50,000 Beam: 70°/40°, Direct/Asymmetric, Glass Clear	Class II	Trailing edge	Surface, Indoor / Outdoor	Ø110 x H35
	Callisto Wall Black 120lm 4000K Ra>80 Trailing edge 3W LED 40 lm/W SDCM:3 L70/B50>50,000 Beam: 70°/40°, Direct/Asymmetric, Glass Clear	IP65 IK06		Screwless terminal block	
	923016	Class II	Trailing edge	Surface, Indoor / Outdoor	Ø110 x H35
	Callisto Wall Graphite 110lm 4000K Ra>80 Trailing edge 3W LED 37 lm/W SDCM:3 L70/B50>50,000 Beam: 70°/40°, Direct/Asymmetric, Glass Clear	IP65 IK06		Screwless terminal block	
 <i>Not released yet</i>	912016	Class II	Trailing edge	Surface, Indoor / Outdoor	Ø110 x D35
	Callisto Wall 120lm 4000K Ra>80 Trailing edge 3W LED 40 lm/W SDCM:3 L70/B50>50,000 Beam: 65°/85°, Direct/Asymmetric, Glass Clear	IP65 IK06		Screwless terminal block	
Accessories					
	790				L106 x W106 x H18
	Callisto Black Reflector				