

Callisto Bollard



Attractive garden lamp for outdoor use. Well integrated LED chip, dimmable via phase-dimming. Made of die-cast powder-coated aluminium, glass diffuser. 60 cm in total height, direct 230 V with loopable quick clips, front locked using torx. IP44, vandal-resistant. Can be screwed to tile or concrete, and embedded using an anchor (accessory)

Callisto Bollard



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 914107 Callisto Pole Black 60lm 2700K Ra>80 Trailing edge 3W LED 20 lm/W SDCM:3 L70/B50>50,000 Beam: 65°/85°, Direct/Asymmetric, Glass Clear	Class I IP44	Trailing edge	Outdoor Screwless terminal block	W180 x H600 x D100
 923107 Callisto Pole Graphite 60lm 2700K Ra>80 Trailing edge 3W LED 20 lm/W SDCM:3 L70/B50>50,000 Beam: 65°/85°, Direct/Asymmetric, Glass Clear	Class I IP44	Trailing edge	Outdoor Screwless terminal block	W180 x H600 x D100
 914005 Callisto Pole Black 110lm 3000K Ra>80 Trailing edge 3W LED 37 lm/W SDCM:3 L70/B50>50,000 Beam: 65°/85°, Direct/Asymmetric, Glass Clear	Class I IP44	Trailing edge	Pole, wall, bollard or earthing rod, Outdoor Screwless terminal block	W180 x H600 x D100
 914105 Callisto Pole Black 60lm 3000K Ra>80 Trailing edge 3W LED 20 lm/W SDCM:3 L70/B50>50,000 Beam: 65°/85°, Direct/Asymmetric, Glass Clear	Class I IP44	Trailing edge	Outdoor Screwless terminal block	W180 x H600 x D100
 923005 Callisto Pole Graphite 110lm 3000K Ra>80 Trailing edge 3W LED 37 lm/W SDCM:3 L70/B50>50,000 Beam: 65°/85°, Direct/Asymmetric, Glass Clear	Class I IP44	Trailing edge	Pole, wall, bollard or earthing rod, Outdoor Screwless terminal block	W180 x H600 x D100
 923105 Callisto Pole Graphite 60lm 3000K Ra>80 Trailing edge 3W LED 20 lm/W SDCM:3	Class I IP44	Trailing edge	Outdoor Screwless terminal block	W180 x H600 x D100

Article codes



Article	L70/B50>50,000	Protection	Control gear	Mounting/Connection	Dimensions
Beam: 65°/85°, Direct/Asymmetric, Glass Clear 	912005 Callisto Pole White 120lm 3000K Ra>80 Trailing edge 3W LED 40 lm/W SDCM:3 L70/B50>50,000 Beam: 65°/85°, Direct/Asymmetric, Glass Clear	Class I IP44	Trailing edge	Pole, wall, bollard or earthing rod, Outdoor Screwless terminal block	W180 x H600 x D100
Accessories					
	600584 Callisto Pole Anchoring set				W180 x H220 x D100