



Round surface-mounted luminaire, wholly uniform light with attractive design, made of powder-coated steel, simple to mount by removing the back plate, which can be screwed on to all known ceiling outlets/ electrical boxes, clips with option of additional looping, connectors between lamp and mounting plate, dimmable driver Phase cut-off/DALI and sensor options. Both visible and hidden cabling possible.

Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>212000 Circulus White 1420lm 2700K Ra>80 Trailing edge 15W LED 95 lm/W SDCM:3 L80/B10>50,000, L70/B50>100,000 Beam: 110°, Direct, Opal</p>	Class I IP21 IK05	Trailing edge	Surface, Innendørs Screwless terminal block	Ø360 x H45
 <p>212003 Circulus White 1360lm 2700K Ra>80 Sensor 19W LED 72 lm/W SDCM:3 L80/B10>50,000, L70/B50>100,000 Beam: 110°, Direct, Opal</p>	Class I IP21 IK05	Sensor	Surface, Innendørs Screwless terminal block	Ø360 x H45
 <p>214000 Circulus Black 1420lm 2700K Ra>80 Trailing edge 15W LED 95 lm/W SDCM:3 L80/B10>50,000, L70/B50>100,000 Beam: 110°, Direct, Opal</p>	Class I IP21 IK05	Trailing edge	Surface, Innendørs Screwless terminal block	Ø360 x H45
 <p>212002 Circulus White 1530lm 3000K Ra>80 DALI-2 / Push Dim 15W LED 102 lm/W SDCM:3 L80/B10>50,000, L70/B50>100,000 Beam: 110°, Direct, Opal</p>	Class I IP21 IK05	DALI-2 / Push Dim	Surface, Innendørs Screwless terminal block	Ø360 x H45
 <p>212001 Circulus White 1530lm 3000K Ra>80 Trailing edge 15W LED 102 lm/W SDCM:3 L80/B10>50,000, L70/B50>100,000 Beam: 110°, Direct, Opal</p>	Class I IP21 IK05	Trailing edge	Surface, Innendørs Screwless terminal block	Ø360 x H45
 <p>212004 Circulus White 1530lm 3000K Ra>80 Sensor 15W LED 102 lm/W SDCM:3 L70/B50>50,000 Beam: 110°, Direct, Opal</p>	Class I IP21 IK05	Sensor	Surface, Innendørs Screwless terminal block	Ø360 x H45

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 214001 Circulus Black 1530lm 3000K Ra>80 Trailing edge 15W LED 102 lm/W SDCM:3 L80/B10>50,000, L70/B50>100,000 Beam: 110°, Direct, Opal	Class I IP21 IK05	Trailing edge	Surface, Innendørs Screwless terminal block	Ø360 x H45