

# Circulus Maxi



Circulus Maxi is a round, surface-mounted luminaire in a minimalistic design that gives a beautiful, uniform light that suits all spaces. Dimmable using a DALI or phase control dimmer. Simple installation with magnetic lock and quick connections between the luminaire and back plate that can be screwed directly into all known ceiling boxes. Visible cabling also possible.

# Circulus Maxi



## Product- and environment images



# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>214014  <b>Circulus Maxi Black 3050lm 3000K</b>  <b>Ra&gt;80 DALI-2 / Push Dim</b>  <b>30W LED</b>            102 lm/W SDCM:3            L70/B10&gt;100,000            Beam: 100°, Direct, Opal</p>	<b>Class II</b> <b>IP21</b> <b>IK05</b>	DALI-2 / Push Dim	Surface, Indoor Screwless terminal block	L550 x W550 x H55
 <p>214018 •  <b>Circulus Maxi Black 3050lm 3000K</b>  <b>Ra&gt;80 Emergency 3H/trailing edge</b>  <b>30W LED</b>            102 lm/W SDCM:3            L70/B10&gt;100,000            Beam: 100°, Direct, Opal</p>	<b>Class II</b> <b>IP21</b> <b>IK05</b>	Emergency 3H/trailing edge	Surface, Indoor Screwless terminal block	L550 x W550 x H55
 <p>214010  <b>Circulus Maxi Black 3050lm 3000K</b>  <b>Ra&gt;80 Trailing edge</b>  <b>30W LED</b>            102 lm/W SDCM:3            L70/B10&gt;100,000            Beam: 100°, Direct, Opal</p>	<b>Class II</b> <b>IP21</b> <b>IK05</b>	Trailing edge	Surface, Indoor Screwless terminal block	Ø550 x H55
 <p>214013  <b>Circulus Maxi White 3120lm 3000K</b>  <b>Ra&gt;80 DALI-2 / Push Dim</b>  <b>30W LED</b>            104 lm/W SDCM:3            L70/B10&gt;100,000            Beam: 100°, Direct, Opal</p>	<b>Class II</b> <b>IP21</b> <b>IK05</b>	DALI-2 / Push Dim	Surface, Indoor Screwless terminal block	Ø550 x H55
 <p>214017 •  <b>Circulus Maxi White 3120lm 3000K</b>  <b>Ra&gt;80 Emergency 3H/trailing edge</b>  <b>30W LED</b>            104 lm/W SDCM:3            L70/B10&gt;100,000            Beam: 100°, Direct, Opal</p>	<b>Class II</b> <b>IP21</b> <b>IK05</b>	Emergency 3H/trailing edge	Surface, Indoor Screwless terminal block	L550 x W550 x H55
 <p>214009  <b>Circulus Maxi White 3120lm 3000K</b>  <b>Ra&gt;80 Trailing edge</b>  <b>30W LED</b>            104 lm/W SDCM:3            L70/B10&gt;100,000            Beam: 100°, Direct, Opal</p>	<b>Class II</b> <b>IP21</b> <b>IK05</b>	Trailing edge	Surface, Indoor Screwless terminal block	Ø550 x H55

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>214016  <b>Circulus Maxi Black 3210lm 4000K</b>  <b>Ra&gt;80 DALI-2 / Push Dim</b>  <b>30W LED</b>            107 lm/W SDCM:3            L70/B10&gt;100,000            Beam: 100°, Direct, Opal</p>	<b>Class II</b> <b>IP21</b> <b>IK05</b>	DALI-2 / Push Dim	Surface, Indoor Screwless terminal block	L550 x W550 x H55
 <p>214020 •  <b>Circulus Maxi Black 3210lm 4000K</b>  <b>Ra&gt;80 Emergency 3H/trailing edge</b>  <b>30W LED</b>            107 lm/W SDCM:3            L70/B10&gt;100,000            Beam: 100°, Direct, Opal</p>	<b>Class II</b> <b>IP21</b> <b>IK05</b>	Emergency 3H/trailing edge	Surface, Indoor Screwless terminal block	L550 x W550 x H55
 <p>214012  <b>Circulus Maxi Black 3210lm 4000K</b>  <b>Ra&gt;80 Trailing edge</b>  <b>30W LED</b>            107 lm/W SDCM:3            L70/B10&gt;100,000            Direct, Opal</p>	<b>Class II</b> <b>IP21</b> <b>IK05</b>	Trailing edge	Surface, Indoor Screwless terminal block	Ø550 x H55
 <p>214015  <b>Circulus Maxi White 3480lm 4000K</b>  <b>Ra&gt;80 DALI-2 / Push Dim</b>  <b>30W LED</b>            116 lm/W SDCM:3            L70/B10&gt;100,000            Beam: 100°, Direct, Opal</p>	<b>Class II</b> <b>IP21</b> <b>IK05</b>	DALI-2 / Push Dim	Surface, Indoor Screwless terminal block	L550 x W550 x H55
 <p>214019 •  <b>Circulus Maxi White 3480lm 4000K</b>  <b>Ra&gt;80 Emergency 3H/trailing edge</b>  <b>30W LED</b>            116 lm/W SDCM:3            L70/B10&gt;100,000            Beam: 100°, Direct, Opal</p>	<b>Class II</b> <b>IP21</b> <b>IK05</b>	Emergency 3H/trailing edge	Surface, Indoor Screwless terminal block	L550 x W550 x H55
 <p>214011  <b>Circulus Maxi White 3480lm 4000K</b>  <b>Ra&gt;80 Trailing edge</b>  <b>30W LED</b>            116 lm/W SDCM:3            L70/B10&gt;100,000            Beam: 100°, Direct, Opal</p>	<b>Class II</b> <b>IP21</b> <b>IK05</b>	Trailing edge	Surface, Indoor Screwless terminal block	Ø550 x H55

## Accessories

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
	820307	<b>Emergency battery 3 Hours 3.0Ah - Model No: B093</b>		L137 x W27 x H27

- = This article is produced by order, with an expected delivery time of 3-4 weeks.