

Curve



Round, attractive wall luminaire for horizontal/vertical installation and indoors/outdoors. Made of die-cast powder-coated aluminium. Glass diffuser. Can be mounted as a down/uplight or as a down or uplight, IP65, integrated LED, mounting back panel with two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. IP65 and vandal-resistant rating IK06.

Curve



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 614340 Curve Black 500lm 2700K Ra>80 Trailing edge 7W LED 71 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Beam: 110°/110°, Direct/Indirect, Glass Clear	Class I IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W320 x H60 x D103
 623340 Curve Graphite 500lm 2700K Ra>80 Trailing edge 7W LED 71 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Beam: 110°/110°, Direct/Indirect, Glass Clear	Class I IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W320 x H60 x D103
 611340 Curve White 580lm 2700K Ra>80 Trailing edge 7W LED 83 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Beam: 110°/110°, Direct/Indirect, Glass Clear	Class I IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W320 x H60 x D103
 614341 Curve Black 520lm 3000K Ra>80 Trailing edge 7W LED 74 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Beam: 110°/110°, Direct/Indirect, Glass Clear	Class I IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W320 x H60 x D103
 623341 Curve Graphite 520lm 3000K Ra>80 Trailing edge 7W LED 74 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Beam: 110°/110°, Direct/Indirect, Glass Clear	Class I IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W320 x H60 x D103
 611341 Curve White 600lm 3000K Ra>80 Trailing edge 7W LED 86 lm/W SDCM:3	Class I IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W320 x H60 x D103

Article codes



Article	L90/B10>50,000, L80/B10>100,000	Protection	Control gear	Mounting/Connection	Dimensions
	Beam: 110°/110°, Direct/Indirect, Glass Clear	Class I	Trailing edge	Surface, Indoor / Outdoor	W320 x H60 x D103
	625942	IP65		Screwless terminal block	
	Curve Graphite 530lm 4000K Ra>80	IK06			
	Trailing edge				
	7W LED				
76 lm/W SDCM:3					
L90/B10>50,000, L80/B10>100,000					
Beam: 110°, Direct/Indirect, Glass					
Clear					
Accessories					
	600002			Indoor / Outdoor	L320 x W271 x H10
	Number Plate 320x271mm				