

# Curve Direct



Round, attractive wall luminaire for horizontal/vertical installation and indoors/outdoors. Made of die-cast powder-coated aluminium. Glass diffuser. Can be mounted as a downlight or as an uplight, IP65, integrated LED, mounting back panel with two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. IP65 and vandal-resistant rating IK06.

# Curve Direct



## Product- and environment images



# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>611396  <b>Curve Direct Black 530lm 2700K</b>  <b>Ra&gt;80 Trailing edge</b>  <b>7W LED</b>            76 lm/W SDCM:3            L90/B10&gt;50,000, L80/B10&gt;100,000            Direct, Glass Frosted</p>	<b>Class I</b> <b>IP65</b> <b>IK06</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W320 x H60 x D103
 <p>611398  <b>Curve Direct Graphite 530lm 2700K</b>  <b>Ra&gt;80 Trailing edge</b>  <b>7W LED</b>            76 lm/W SDCM:3            L90/B10&gt;50,000, L80/B10&gt;100,000            Direct, Glass Frosted</p>	<b>Class I</b> <b>IP65</b> <b>IK06</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W320 x H60 x D103
 <p>611365  <b>Curve Direct White 345lm 2700K</b>  <b>Ra&gt;80 Trailing edge</b>  <b>10W LED</b>            35 lm/W SDCM:3            L70/B10&gt;50,000            Beam: 110°, Direct, Glass Clear</p>	<b>Class I</b> <b>IP65</b> <b>IK06</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W320 x H60 x D103
 <p>611397  <b>Curve Direct Black 550lm 3000K</b>  <b>Ra&gt;80 Trailing edge</b>  <b>7W LED</b>            79 lm/W SDCM:3            L90/B10&gt;50,000, L80/B10&gt;100,000            Direct, Glass Frosted</p>	<b>Class I</b> <b>IP65</b> <b>IK06</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W320 x H60 x D103
 <p>611399  <b>Curve Direct Graphite 550lm 3000K</b>  <b>Ra&gt;80 Trailing edge</b>  <b>7W LED</b>            79 lm/W SDCM:3            L90/B10&gt;50,000, L80/B10&gt;100,000            Direct, Glass Frosted</p>	<b>Class I</b> <b>IP65</b> <b>IK06</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W320 x H60 x D103
 <p>611395  <b>Curve Direct White 550lm 3000K</b>  <b>Ra&gt;80 Trailing edge</b>  <b>7W LED</b>            79 lm/W SDCM:3            L90/B10&gt;50,000, L80/B10&gt;100,000            Direct, Glass Frosted</p>	<b>Class I</b> <b>IP65</b> <b>IK06</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W320 x H60 x D103

## Accessories

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 600002 Number Plate 320x271mm			Indoor / Outdoor	L320 x W271 x H10