



Attractive, square wall luminaire for horizontal/vertical installation and indoors/outdoors. Made of die-cast powder-coated aluminium. Glass diffuser. Can be mounted as a down/uplight or as a down or uplight, IP65, integrated LED, mounting back panel with two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. IP65 and vandal-resistant rating IK06.

Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 614350 Edge Black 560lm 2700K Ra>80 Trailing edge 7W LED 80 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Beam: 110°/110°, Direct/Indirect, Glass Clear	Class I IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W320 x H60 x D103
 623350 Edge Graphite 560lm 2700K Ra>80 Trailing edge 7W LED 80 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Beam: 110°/110°, Direct/Indirect, Glass Clear	Class I IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W320 x H60 x D103
 611350 Edge White 595lm 2700K Ra>80 Trailing edge 10W LED 60 lm/W SDCM:3 L70/B10>50,000 Beam: 110°/110°, Direct/Indirect, Glass Clear	Class I IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W320 x H60 x D103
 614351 Edge Black 580lm 3000K Ra>80 Trailing edge 7W LED 83 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Beam: 110°/110°, Direct/Indirect, Glass Clear	Class I IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W320 x H60 x D103
 623351 Edge Graphite 580lm 3000K Ra>80 Trailing edge 7W LED 83 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Beam: 110°/110°, Direct/Indirect, Glass Clear	Class I IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W320 x H60 x D103
 611351 Edge White 660lm 3000K Ra>80 Trailing edge 7W LED 94 lm/W SDCM:3	Class I IP65 IK06	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W320 x H60 x D103

Article codes



Article	L90/B10>50,000, L80/B10>100,000	Protection	Control gear	Mounting/Connection	Dimensions
	Beam: 110°/110°, Direct/Indirect, Glass Clear	Class I	Trailing edge	Surface, Indoor / Outdoor	W320 x H60 x D103
	625952	IP65		Screwless terminal block	
	Edge Graphite 590lm 4000K Ra>80	IK06			
	Trailing edge				
	7W LED				
84 lm/W SDCM:3					
L90/B10>50,000, L80/B10>100,000					
Beam: 110°/110°, Direct/Indirect, Glass Clear					
Accessories					
	600002			Indoor / Outdoor	L320 x W271 x H10
	Number Plate 320x271mm				