



Round lamp in several sizes. Vandal-resistant with impact-resistant polycarbonate opalescent diffuser. The whole luminaire has been approved for common access routes and has vandal-resistant rating IK10. KI II, two cable inputs and the option of additional looping using the integrated quick clips. Can be mounted to either the wall or ceiling with both concealed and visible cabling. Many light source variants and sensors, wireless control and emergency light.


Econ



Product- and environment images





| Article | | Protection | Control gear | Mounting/Connection | Dimensions |
|---|--|----------------------------|---------------|--------------------------|------------|
|  | 111894 | Class II | Sensor | Surface, Indoor | Ø280 x H85 |
| | Econ White E27 500lm 2700K Ra>80 | IP21 ceiling / IP20 | | Screwless terminal block | |
| | Sensor | wall | | | |
| | 10W LED | IK10 | | | |
| | 50 lm/W SDCM:6 | | | | |
| | L70/B50>50,000 | | | | |
| | Beam: 120°, Direct, Opal | | | | |
|  | 111893 | Class II | Trailing edge | Surface, Indoor | Ø280 x H85 |
| | Econ White E27 500lm 2700K Ra>80 | IP21 ceiling / IP20 | | Screwless terminal block | |
| | Trailing edge | wall | | | |
| | 10W LED | IK10 | | | |
| | 50 lm/W SDCM:6 | | | | |
| | L70/B50>50,000 | | | | |
| | Beam: 120°, Direct, Opal | | | | |