



Attractive downlight for indoor or outdoor use under eaves, 30-degree 360-degree stepless tilt. Mounted directly on ceiling or on known ceiling electrical boxes. Well integrated LED chip with DimToWarm 2800K-2000K via phase-dimming. Made of die-cast powder-coated aluminium, glass diffuser. 42-degree beam angle angle via reflector. Quick connection between luminaire body and ceiling mounting plate. Luminaire body is snapped into place and secured using two concealed internal screws.

Product- and environment images



Cube DimToWarm



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	906213 Cube DimToWarm Black DimToWarm 490lm 2000-2800K Ra>95 Trailing edge 7.3W LED 67 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Direct, Reflector	Class I IP21	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L132 x W132 x H65
	906233 Cube DimToWarm 2X Black DimToWarm 980lm 2000-2800K Ra>95 Trailing edge 14.8W LED 66 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Direct, Reflector	Class I IP21	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L231 x W132 x H65
	906211 Cube White DimToWarm 550lm 2000-2800K Ra>95 Trailing edge 7.3W LED 75 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Direct, Reflector	Class I IP21	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L132 x W132 x H65
	906231 Cube 2X White DimToWarm 1100lm 2000-2800K Ra>95 Trailing edge 14.8W LED 74 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Direct, Reflector	Class I IP21	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L231 x W132 x H65