

# Cube DimToWarm



Attractive downlight for indoor or outdoor use under eaves, 30-degree 360-degree stepless tilt. Mounted directly on ceiling or on known ceiling electrical boxes. Well integrated LED chip with DimToWarm 2800K-2000K via phase-dimming. Made of die-cast powder-coated aluminium, glass diffuser. 42-degree beam angle via reflector. Quick connection between luminaire body and ceiling mounting plate. Luminaire body is snapped into place and secured using two concealed internal screws.

# Cube DimToWarm



## Product- and environment images





# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>906213</p> <p><b>Cube DimToWarm Black</b></p> <p><b>DimToWarm 490lm 2000-2800K</b></p> <p><b>Ra&gt;95 Trailing edge</b></p> <p><b>7.3W LED</b></p> <p>67 lm/W SDCM:3</p> <p>L90/B10&gt;50,000</p> <p>Beam: 42°, Direct, Reflector</p>	<p><b>Class I</b></p> <p><b>IP21</b></p>	Trailing edge	Surface, Indoor / Outdoor	L132 x W132 x H65
 <p>906233</p> <p><b>Cube DimToWarm Black</b></p> <p><b>DimToWarm 980lm 2000-2800K</b></p> <p><b>Ra&gt;95 Trailing edge</b></p> <p><b>14.8W LED</b></p> <p>66 lm/W SDCM:3</p> <p>L90/B10&gt;50,000</p> <p>Beam: 42°, Direct, Reflector</p>	<p><b>Class I</b></p> <p><b>IP21</b></p>	Trailing edge	Surface, Indoor / Outdoor	L231 x W132 x H65
 <p>906211</p> <p><b>Cube White DimToWarm 550lm</b></p> <p><b>2000-2800K Ra&gt;95 Trailing edge</b></p> <p><b>7.3W LED</b></p> <p>75 lm/W SDCM:3</p> <p>L90/B10&gt;50,000</p> <p>Beam: 42°, Direct, Reflector</p>	<p><b>Class I</b></p> <p><b>IP21</b></p>	Trailing edge	Surface, Indoor / Outdoor	L132 x W132 x H65
 <p>906231</p> <p><b>Cube White DimToWarm 1100lm</b></p> <p><b>2000-2800K Ra&gt;95 Trailing edge</b></p> <p><b>14.8W LED</b></p> <p>74 lm/W SDCM:3</p> <p>L90/B10&gt;50,000</p> <p>Beam: 42°, Direct, Reflector</p>	<p><b>Class I</b></p> <p><b>IP21</b></p>	Trailing edge	Surface, Indoor / Outdoor	L231 x W132 x H65