

# Junistar Lux



The optimal downlight on the market for indoor use. Junistar Lux emits a harmonious, non-flickering light with excellent colour rendering. Its patented, adjustable 30-degree tilt function in all directions is covered by a 10-year warranty. It includes a junction box that provides strain relief for several types of cables, as well as fixation for plastic tubing.

# Junistar Lux



## Product- and environment images



# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>902515  <b>Junistar Lux Black 580lm 2700K Ra 98 DALI-2 8W LED</b>            73 lm/W SDCM:1            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP44/IP20</b>	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	Ø94 x H50
 <p>902506  <b>Junistar Lux Black 580lm 2700K Ra 98 Trailing edge 8W LED</b>            73 lm/W SDCM:1            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP44/IP20</b>	Trailing edge	Recessed, Indoor Screwless terminal block	Ø94 x H50
 <p>902234  <b>Junistar Lux Black/Gold 530lm 2700K Ra 98 Trailing edge 8W LED</b>            66 lm/W SDCM:1            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP44/IP20</b>	Trailing edge	Recessed, Indoor Screwless terminal block	Ø94 x H50
 <p>902512  <b>Junistar Lux Brushed steel 580lm 2700K Ra 98 DALI-2 8W LED</b>            73 lm/W SDCM:1            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP44/IP20</b>	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	Ø94 x H50
 <p>902503  <b>Junistar Lux Brushed steel 580lm 2700K Ra 98 Trailing edge 8W LED</b>            73 lm/W SDCM:1            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP44/IP20</b>	Trailing edge	Recessed, Indoor Screwless terminal block	Ø94 x H50
 <p>902509  <b>Junistar Lux White 580lm 2700K Ra 98 DALI-2 8W LED</b>            73 lm/W SDCM:1            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP44/IP20</b>	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	Ø94 x H50

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>902500  <b>Junistar Lux White 540lm 2700K Ra 98 Trailing edge</b>  <b>8W LED</b>            68 lm/W SDCM:1            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP44/IP20</b>	Trailing edge	Recessed, Indoor Screwless terminal block	Ø94 x H50
 <p>902516  <b>Junistar Lux Black 590lm 3000K Ra 98 DALI-2</b>  <b>8W LED</b>            74 lm/W SDCM:1            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP44/IP20</b>	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	Ø94 x H50
 <p>902507  <b>Junistar Lux Black 590lm 3000K Ra 98 Trailing edge</b>  <b>8W LED</b>            74 lm/W SDCM:1            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP44/IP20</b>	Trailing edge	Recessed, Indoor Screwless terminal block	Ø94 x H50
 <p>902235  <b>Junistar Lux Black/Gold 540lm 3000K Ra 98 Trailing edge</b>  <b>8W LED</b>            68 lm/W SDCM:1            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP44/IP20</b>	Trailing edge	Recessed, Indoor Screwless terminal block	Ø94 x H50
 <p>902504  <b>Junistar Lux Brushed steel 590lm 3000K Ra 98 Trailing edge</b>  <b>8W LED</b>            74 lm/W SDCM:1            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP44/IP20</b>	Trailing edge	Recessed, Indoor Screwless terminal block	Ø94 x H50
 <p>902510  <b>Junistar Lux White 590lm 3000K Ra 98 DALI-2</b>  <b>8W LED</b>            74 lm/W SDCM:1            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP44/IP20</b>	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	Ø94 x H50

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>902501  <b>Junistar Lux White 590lm 3000K Ra</b>  <b>98 Trailing edge</b>  <b>8W LED</b>            74 lm/W SDCM:1            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP44/IP20</b>	Trailing edge	Recessed, Indoor Screwless terminal block	Ø94 x H50
 <p>902517  <b>Junistar Lux Black 620lm 4000K Ra</b>  <b>98 DALI-2</b>  <b>8W LED</b>            78 lm/W SDCM:1            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP44/IP20</b>	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	Ø94 x H50
 <p>902508  <b>Junistar Lux Black 620lm 4000K Ra</b>  <b>98 Trailing edge</b>  <b>8W LED</b>            78 lm/W SDCM:1            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP44/IP20</b>	Trailing edge	Recessed, Indoor Screwless terminal block	Ø94 x H50
 <p>902505  <b>Junistar Lux Brushed steel 620lm</b>  <b>4000K Ra 98 Trailing edge</b>  <b>8W LED</b>            78 lm/W SDCM:1            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP44/IP20</b>	Trailing edge	Recessed, Indoor Screwless terminal block	Ø94 x H50
 <p>902511  <b>Junistar Lux White 620lm 4000K Ra</b>  <b>98 DALI-2</b>  <b>8W LED</b>            78 lm/W SDCM:1            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP44/IP20</b>	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	Ø94 x H50
 <p>902502  <b>Junistar Lux White 620lm 4000K Ra</b>  <b>98 Trailing edge</b>  <b>8W LED</b>            78 lm/W SDCM:1            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP44/IP20</b>	Trailing edge	Recessed, Indoor Screwless terminal block	Ø94 x H50

## Accessories

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 768 <b>IsoSafe Cup Black IsoSafe Cover</b>				L55 x W75 x H55
 9143 <b>Rehab Ring Black 133mm for Junistar, Uniled, Soft &amp; Jupiter</b>				Ø133 x H4
 9236 <b>Rehab Ring Black 180mm for Junistar, Uniled, Soft &amp; Jupiter</b>				Ø180 x H45
 9427 <b>Rehab Ring Black 250mm for Junistar, Uniled, Soft &amp; Jupiter</b>				Ø250 x H45
 9973 <b>Rehab Ring Brushed steel 133mm for Junistar, Uniled, Soft &amp; Jupiter</b>				Ø133 x H4
 9974 <b>Rehab Ring Brushed steel 180mm for Junistar, Uniled, Soft &amp; Jupiter</b>				Ø180 x H45
 9233 <b>Rehab Ring Graphite 133mm for Junistar, Uniled, Soft &amp; Jupiter</b>				Ø133 x H4
 9234 <b>Rehab Ring Graphite 180mm for Junistar, Uniled, Soft &amp; Jupiter</b>				Ø180 x H45
 9327 <b>Rehab Ring Graphite 250mm for Junistar, Uniled, Soft &amp; Jupiter</b>				Ø250 x H45
 9223 <b>Rehab Ring White 133mm for Junistar, Uniled, Soft &amp; Jupiter</b>				Ø133 x H4
 9224 <b>Rehab Ring White 180mm for Junistar, Uniled, Soft &amp; Jupiter</b>				Ø180 x H45
 9227 <b>Rehab Ring White 250mm for Junistar, Uniled, Soft &amp; Jupiter</b>				Ø250 x H45
 820489 <b>Sensor Dim Box White 200VA</b>				L220 x W75 x H34

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 8246094429 <b>Emergencybox Driver DALI / EM Self test, DALI Emergency 3 hours</b>				L270 x W75 x H35
 820090 <b>Emergencybox Adapter kit for downlight</b>				L250 x W13 x H13
 8246094364 <b>Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours</b>				L270 x W75 x H35
 8246094500 <b>Emergencybox Driver DALI / EM DALI/Self test, Emergency 3 hours</b>				L270 x W75 x H35